

Feed-through terminals RK | Protective earth terminals SL

Screw connection system	SL 4/35	RK 6-10	RK 6-10/35
 <ul style="list-style-type: none"> • Foot can be snapped on TS 32 and TS 35 DIN rails • Housing made from polyamide 6.6 UL 94-V2 	 <p>M 3</p>	 <p>M 4</p>	 <p>M 4</p>
Connection diagram	 <p>Protective earth terminal 2 connections</p>	 <p>Feed-through terminal 2 connections</p>	 <p>Feed-through terminal 2 connections</p>
Connection type	Screw connection	Screw connection	Screw connection
Size (L x W x H) mm with TS 32 mm		48 x 8 x 51.5	
Size (L x W x H) mm with TS 35 x 7.5 mm	56 x 8 x 47	48 x 8 x 47	48 x 8 x 47
Type	Qty.	Qty.	Qty.
Type colour	SL 4/35 GNYE	RK 6-10 BG	RK 6-10/35 BG
Cat. no.	1212.2	1005.2	1578.2
Type colour		RK 6-10 BU	RK 6-10/35 BU
Cat. no.		1005.5	1578.5
Type colour			
Cat. no.			
Type colour			
Cat. no.			
Colours available			
Rated specifications acc. to	IEC	UL	cUL
Rated voltage, V			
Rated current, A			
Rated wire cross-section, mm ² AWG		4 22-11	
Rated impulse voltage, kV Contamination degree		8 3	
Plug gauge acc. to EN 60 947-1 Flamm. class acc. to UL 94		A4 V2	
Connection data			
Single wire (solid) / Stranded mm ²		0.2-6 -	
Stranded/stranded (w/ferrules acc. to DIN 46 228/1) mm ²		0.2-6 0.2-4	
Contact wire range, mm ²		0.2-6	
Stripping length, mm		12	
Torque, Nm Screw		0.5-1.0 Slotted M 3	
Special connection, mm			
Features			
Material of insulated housing Temperature range		PA 6.6 -40 to +105°C	
Number of cross-connection channels Test pick-off		1 1	
Accessories	Page	Qty.	Page
End plate AP			
Cat. no.			
Partition plate TW			
Cat. no.			
Insulation plate TRS			
Cat. no.			
Cross-connector Q			
Cat. no.			
Cross-connector Q / Insulated cross-connector QI			
Cat. no.			
Insulated cross-connection QI			
Cat. no.			
Cross-connector Q			
Cat. no.			
Insulated cross-connection QI			
Cat. no.			
Cross-connector Q			
Cat. no.			
Insulated cross-connection QI			
Cat. no.			
Cross-connector Q			
Cat. no.			
End stop ES			
Cat. no.			
Test adapter TA			
Cat. no.			
Screwdriver SDB			
Cat. no.			
Quick marking PMC SB			
Cat. no.			