



P.C. board plug-in connectors
 Connector


5,08 mm

PKB 1100/... /5,08

PKB 1110/... /5,08

Drawings
Connection principle
Dimensions

 Spacing mm
 Insulation stripping length mm
 PCB hole diameter mm

Connection data

 Single wire (solid) mm²
 Stranded wire (flexible) mm²
 Stranded wire (with ferrules) mm²
Output information

	300 V	250 V
Rated voltage V	300 V	250 V
Rated current A	15 A	12 A (T60)
Cross section max. AWG/mm ²	22-10	2,50
Rated surge voltage	—	4,00 kV
Rated torque/Screw size	—	0,50 Nm/M3
Contamination degree	—	3

Materials

	PA 6.6 V0 / UL 94 V0
Insulating material/Flammability class	PA 6.6 V0 / UL 94 V0
Temperature Range	-30°C / +105°C
Clamping part	CuZn
Clamping cage/Eccentric	—
Contact pin	—
Cage tension spring	—
Wire protection	—
Soldering lug	—
Contact Spring	CuSn

Order information

 Standard colour(s)
 (further colours on request, see page 5)

Strain-relief-clamp

5,08

7,00

—

2,50

2,50

2,50



300 V

15 A

22-10

—

—

—



250 V

12 A (T60)

2,50

4,00 kV

0,50 Nm/M3

3

Strain-relief-clamp

5,08

7,00

—

2,50

2,50

2,50



300 V

15 A

22-10

—

—

—



250 V

12 A (T60)

2,50

4,00 kV

0,50 Nm/M3

3

PA 6.6 V0 / UL 94 V0

-30°C / +105°C

CuZn

—

—

—

—

—

—

CuSn

No. of poles	Cat.-No.	Qty.p.pck.
	●	
	green	
	(Ral 6018)	
2	11305.1	50
3	11306.1	50
4	11307.1	50
5	11308.1	50
6	11309.1	50
7	11310.1	50
8	11311.1	50
9	11312.1	50
10	11313.1	50
11	11314.1	50
12	11315.1	50
13	11316.1	50
14	11317.1	50
15	11318.1	50
16	11319.1	50

 green
 (Ral 6018)

No. of poles	Cat.-No.	Qty.p.pck.
2	11305.1	50
3	11306.1	50
4	11307.1	50
5	11308.1	50
6	11309.1	50
7	11310.1	50
8	11311.1	50
9	11312.1	50
10	11313.1	50
11	11314.1	50
12	11315.1	50
13	11316.1	50
14	11317.1	50
15	11318.1	50
16	11319.1	50

No. of poles	Cat.-No.	Qty.p.pck.
	●	
	green	
	(Ral 6018)	
2	11339.1	50
3	11340.1	50
4	11341.1	50
5	11342.1	50
6	11343.1	50
7	11344.1	50
8	11345.1	50
9	11346.1	50
10	11347.1	50
11	11348.1	50
12	11349.1	50
13	11350.1	50
14	11351.1	50
15	11352.1	50
16	11353.1	50

 green
 (Ral 6018)

No. of poles	Cat.-No.	Qty.p.pck.
2	11339.1	50
3	11340.1	50
4	11341.1	50
5	11342.1	50
6	11343.1	50
7	11344.1	50
8	11345.1	50
9	11346.1	50
10	11347.1	50
11	11348.1	50
12	11349.1	50
13	11350.1	50
14	11351.1	50
15	11352.1	50
16	11353.1	50

Accessories

Marking	Page 126 - 129
Coding	Page 124 - 125

Page 126 - 129
Page 124 - 125