

MATERIAL SPECIFICATIONS

RECOMMENDED

BASE METAL - CDA-210, EXTRA SPRING TEMPER

PLATING - 0.005±0.0025 MM THICK TIN

MINIMUMS

ELECTRICAL CONDUCTIVITY - ≥20% IACS AT 20°C; USE OF A MATERIAL WITH CONDUCTIVITY <20% IACS MUST BE APPROVED BY PACKARD ELECTRIC MATERIALS ENGINEERING.

TENSILE STRENGTH - 407 MPa

PLATING - FOR LOW ENERGY (≤5v) AND NON-PASSENGER COMPARTMENT POWER CIRCUITS, 0.005±0.0025 MM THICK TIN. FOR MATERIALS CONTAINING 10% OR MORE ZINC, AN UNDERPLATE OF COPPER 0.005±0.0025 MM THICK IS REQUIRED.



TYPE 101 & 105



SECTION A-A

TYPE 102
SAME AS TYPE 101
EXCEPT AS SHOWN
SCALE 2:1

TYPE 103
SAME AS TYPE 101
EXCEPT AS SHOWN
SCALE 2:1



TYPE 104
SAME AS TYPE 101
EXCEPT AS SHOWN
SCALE 2:1





SECTION B-B

MATING BLADE INFORMATION

SCALE 8:1



TYPE 102
SAME AS TYPE 101
EXCEPT AS SHOWN

TYPE 103
SAME AS TYPE 101
EXCEPT AS SHOWN

TYPE 104
SAME AS TYPE 101
EXCEPT AS SHOWN

TYPE 105
SAME AS TYPE 101
EXCEPT AS SHOWN





TYPE 101



MATING PART INFORMATION

SCALE 4:1



OPTIONAL CONSTRUCTION

ALL TYPES

NOTES

1. UNLESS OTHERWISE SPECIFIED AND/OR INDICATED:

   DIMENSIONS ARE TO FACE OF VIEW SHOWN AND AUTOMATICALLY ROUNDED BY COMPUTER FOR INSPECTION (SEE MATH MODEL FOR PRECISE DIMENSIONS). FOR ALL OTHER DIMENSIONS NOT SHOWN BUT REQUIRED FOR TOOL BUILD, SEE MATH MODEL FOR PRECISE TOOL PATH DATA.

2. WHEN PARTS ARE SHIPPED, THEY MUST BE PACKED IN PLASTIC BAGS OR SHIPPING CONTAINERS MUST BE LINED WITH PLASTIC LINERS. BAGS OR LINERS MUST BE SEALED TO AVOID ENTRY OF FOREIGN MATTER.

3. SEALING CODE 3 - DESIGN WILL PASS SALT FOG AND IMMERSION TEST AFTER CONDITIONING AS SPECIFIED IN ESA-644 (WEATHER-PACK), ESA-710 (METRI-PACK), ESA-650 (UNDERHOOD MICRO-PACK), C-4006 (WORLD CONNECTOR), ETC WHEN MATED TO MATING PART OR EQUIVALENT

4. SEE CABLE SEAL AND SECONDARY LOCK DRAWINGS FOR COMPATIBLE CABLE O.D. RANGE.

5. MINIMUM RETENTION OF PERIPHERAL SEAL TO CONNECTOR IS 4.1 N.

6. SILICONE T-76 ADHESIVE OR EQUIVALENT TO BE APPLIED TO THIS ASSEMBLY FOR THE PURPOSE OF MAINTAINING SEAL POSITION, AND INSURING THAT MINIMUM RETENTION VALUE OF SEAL TO CONNECTOR IS ACHIEVED. SEE GRAPHICS FOR PREFERRED LOCATIONS OF ADHESIVE APPLICATION. THE APPLICATION OF ADHESIVE IS DESIGNATED BY " ● " IN THE TABLE.

7. THIS PRODUCT IS NOT CATEGORIZED AS AN APPEARANCE ITEM, MINOR IMPERFECTIONS INCLUDING, BUT NOT LIMITED TO, FLOW MARKS, COLOR BLEMISHES, GATE VESTIGE, AND SOFT FLASH THAT DO NOT AFFECT THE FIT, FORM, OR FUNCTION OF THE PART ARE PERMISSIBLE PER NAP 4.10-18.

8. FOR APPLICATION DATA SEE THE INDIVIDUAL APPLICATION DRAWINGS.

PART NO	REV	N/P	STATUS	TYPE	CONNECTOR	SEAL	ADHV	REPLACED BY
15324167	A	-	OBSOLETE	103	15324168	15324169	-	-
12124647	B5	-	-	105	12124017	12047939	●	12124647
12124013	D	-	OBSOLETE	105	12124017	12047939	-	-
12092494	B3	-	OBSOLETE	104	12092493	12047939	-	-
12052600	B9	-	-	103	12052499	12047939	-	-
12047938	B9	-	-	102	12047934	12047939	-	-
12047937	B9	-	-	101	12047932	12047939	-	-

SYMBOL DEFINITION			MISSING SYMBOLS
A DIMENSION WITHOUT AN INSPECTION REPORT SYMBOL ( ) DOES NOT REQUIRE INSPECTION. IT MAY BE CONTROLLED ON THE INDIVIDUAL COMPONENT DRAWING.	TOTAL NO OF INSPECTIONS REQUIRED	22	NO MISSING SYMBOL NUMBER
	LAST NO. USED	16	

DWG STATUS DATE	STA	REV	N/P	CHG	ZONE	REVISION HISTORY	AUTH	DR	APVD 1	APVD 2
28FEB1	R	01	-	-		ALL ACTIVE PARTS - REDRAWN TO PD	207269	JLZ	JVP	DMC
13DC95	R	02	-	-		12092493 - CONN BODY COLOR WAS NATURAL	273384	MDH	JWC	EST
12MR07	R	03	-	-		12124647, 12052600, 12047938 & 12047937 - UPDATED PDM ATTRIBUTES; 12092494 - OBSOLETE	400766	RTV	JAA	JDS
25JA08	R	04	-	-		ALL ACTIVE PARTS - ADDED "SHT 1 OF 2". CREATED APPLICATION DRAWING	403544	SDS	DDL	SGS
16DEC8	R	05	-	-		ALL ACTIVE PARTS - 2X 18 +0.15/-0.36 WAS 2X 18	407045	RHB	JAA	RHB
14JA10	R	06	-	-		ALL ACTIVE PARTS - 2X 6 +0.15/-0.22 WAS 2X 6±0.15 AND 2X 12 +0.15/-0.28 WAS 2X 12±0.15	409729	FRE	FRE	GEM

NOTES

1. UNLESS OTHERWISE SPECIFIED AND/OR INDICATED:

   DIMENSIONS ARE TO FACE OF VIEW SHOWN AND AUTOMATICALLY ROUNDED BY COMPUTER FOR INSPECTION (SEE MATH MODEL FOR PRECISE DIMENSIONS). FOR ALL OTHER DIMENSIONS NOT SHOWN BUT REQUIRED FOR TOOL BUILD, SEE MATH MODEL FOR PRECISE TOOL PATH DATA.

2. RECOMMENDED MATERIAL: GLASS FILLED NYLON OR POLYESTER.

3. TERMINAL MUST WITHSTAND A MINIMUM PUSHOUT FORCE OF 89 N (20 LBS).

4. WHEN USING THIS INFORMATION FOR A NEW DESIGN, REQUEST THE LATEST COPY OF THIS PRINT FROM PACKARD ELECTRIC.



DELPHI

DELPHI PACKARD ELECTRICAL/ELECTRONIC ARCHITECTURE
WARREN, OH

DWG TYPE: PART DRAWING

STYLE

VOLUME (CUM): SYSTEM CODE: D

UNLESS OTHERWISE SPECIFIED
THIS DOCUMENT IS IN ACCORDANCE WITH ASME Y14.5M-1994 AS INTERPRET BY THE IN GLOBAL DIMENSIONING AND TOLERANCING STANDARD. ALL DIMENSIONS ARE APPLICABLE TO FEATURES AFTER ANY PLATING. ALL DIMENSIONS ARE TO BE MADE INDEPENDENTLY WITHOUT REGARD TO FEATURES NOT SHOWN. DIMENSIONS ARE TO BE MADE WITHOUT REGARD TO FLEXIBILITY OF SUCH REFERENCES.

ALL DIMENSIONS ARE IN MILLIMETERS

REFERENCE

	DATE
DR	
APVD1 R. BALDWIN	02NOV07
APVD2 F. HESION	1NOV07
APVD3 R. PETROSKY	1NOV07
APVD4	
APVD5	

SUBSTANCES OF CONCERN: NO RECYCLED CONTENT PER DELPHI (294900)

MATL: SEE INDIVIDUAL DRAWING

DRAWING NAME: TAXI ASM CONN F M/P 150 SLD

DRAWING NUMBER: 12077523

SIZE A1x3 | SCALE 2:1 | SHEET NO 1 OF 2 | TOTAL 2 OF 2 | REV R | CHG 06

(16) PROCESS SENSITIVE DIMENSION

DIMENSIONS ENCLOSED IN ( ) INDICATE REFERENCE DIMENSIONS, NO QC TOLERANCE LIMITS ARE ESTABLISHED

| DIMENSIONAL RANGES (MM) | | |