


**Three-level terminals IKD/DLI | Motor connection terminal VMAK**

**Screw connection system**



- Foot can be snapped on TS 32 and TS 35 DIN rails
- Housing made from polyamide 6.6 UL 94-V2

**Connection diagram**

IKD 2.5	IKD 2.5/Q	IKD 2.5/F
Feed-through terminal 3x2 connections	Feed-through terminal 3x2 connections	Feed-through terminal 3x2 connections

**Connection type**

Size (L x W x H) mm with TS 32 mm  
Size (L x W x H) mm with TS 35 x 7.5 mm

**Type**

Type colour

**Cat. no.**

Type colour

**Cat. no.**

Type colour

**Cat. no.**

Type colour

**Cat. no.**

Colours available

**Rated specifications acc. to**

Rated voltage, V

Rated current, A

Rated wire cross-section, mm<sup>2</sup> | AWG

Rated impulse voltage, kV | Contamination degree

Plug gauge acc. to EN 60 947-1 | Flamm. class acc. to UL 94

**Connection data**

Single wire (solid) / Stranded mm<sup>2</sup>

Stranded/stranded (w/ferrules acc. to DIN 46 228/1) mm<sup>2</sup>

Contact wire range, mm<sup>2</sup>

Stripping length, mm

Torque, Nm | Screw

Special connection, mm

**Features**

Material of insulated housing | Temperature range

Number of cross-connection channels | Test pick-off

**Accessories**

End plate AP

**Cat. no.**

Insulation plate TRS

**Cat. no.**

Cross-connector Q

**Cat. no.**

Insulated cross-connector AQI

**Cat. no.**

Cross-connector Q

**Cat. no.**

Insulated cross-connector AQI

**Cat. no.**

Cross-connector Q

**Cat. no.**

Insulated cross-connector AQI

**Cat. no.**

End stop ES

**Cat. no.**

Socket plug STB

**Cat. no.**

Test plug PS

**Cat. no.**

Screwdriver SDB

**Cat. no.**

Quick marking PMC SB

**Cat. no.**

**Screw connection**

84.8 x 5 x 62.8

84.8 x 5 x 58.3

**Qty.**

IKD 2.5 BG

**1261.2**

IKD 2.5 BU

**1261.5**

② ⑤

IEC

CSAus

CSA

250

300

300

24

20

20

2.5 | 22-14

4 | 3

A3 | V2

0.2-4 | -

0.2-4 | 0.2-2.5

0.2-4

7

0.4-0.8 | Slotted M 2.5

-

**Screw connection**

84.8 x 5 x 62.8

84.8 x 5 x 58.3

**Qty.**

IKD 2.5/Q BG

**2268.2**

IKD 2.5/Q BU

**2268.5**

② ⑤

IEC

CSAus

CSA

250

300

300

24

20

20

2.5 | 22-14

4 | 3

A3 | V2

0.2-4 | -

0.2-4 | 0.2-2.5

0.2-4

7

0.4-0.8 | Slotted M 2.5

-

**Screw connection**

84.8 x 5 x 62.8

84.8 x 5 x 58.3

**Qty.**

IKD 2.5/F BG

**1295.2**

②

IEC

CSAus

CSA

250

300

300

24

20

20

2.5 | 22-14

4 | 3

A3 | V2

0.2-4 | -

0.2-4 | 0.2-2.5

0.2-4

7

0.4-0.8 | Slotted M 2.5

-