

## Straight Through – PG External Thread Polyamide (PA)



- Protection Rating: IP68; NEMA 4X
- Pressure Rating: 10Bar; 140psi
- Selection of 2 Insert Materials
- Order Seal Rings and Locknuts Separately
- Standard Colors: Beige or Black

### Polyamide (PA) Beige



### With Thermoplastic Elastomer (TPE) Tubular Sealing Insert

Material Specifications	
<b>Body</b>	Polyamide (PA)
<b>Insert</b>	Thermoplastic Elastomer (TPE)
<b>Temperature Range</b>	
<b>Body</b>	-20 to 100°C (-4 to 212°F)
<b>Insert</b>	-40 to 130°C (-40 to 266°F)
<b>Insert Color</b>	Various

Size	Cable Dia.		Mtg. Hole Dia.		Std. Pk.	Sealing Insert Color	Cat. No. Beige
	mm	(in.)	mm	(in.)			
PG7	4.0-6.5	(.16-.26)	12.5	(.49)	50	Yellow	20033.0
PG9	4.0-6.5	(.16-.26)	15.2	(.60)	50	Yellow	20000.0
PG9	5.0-8.0	(.20-.31)	15.2	(.60)	50	Gray	20001.0
PG9	6.5-9.5	(.26-.37)	15.2	(.60)	50	Black	20002.0
PG11	4.0-6.5	(.16-.26)	18.5	(.73)	50	Yellow	20003.0
PG11	5.0-8.0	(.20-.31)	18.5	(.73)	50	Gray	20004.0
PG11	6.5-9.5	(.26-.37)	18.5	(.73)	50	Black	20005.0
PG11	7.0-10.5	(.28-.41)	18.5	(.73)	50	Green	20006.0
PG13.5	4.0-6.5	(.16-.26)	20.5	(.81)	50	Yellow	20007.0
PG13.5	5.0-8.0	(.20-.31)	20.5	(.81)	50	Gray	20008.0
PG13.5	6.5-9.5	(.26-.37)	20.5	(.81)	50	Black	20009.0
PG13.5	7.0-10.5	(.28-.41)	20.5	(.81)	50	Green	20010.0
PG13.5	9.0-13.0	(.35-.51)	20.5	(.81)	50	Red	20011.0
PG16	4.0-6.5	(.16-.26)	22.5	(.89)	25	Yellow	20012.0
PG16	5.0-8.0	(.20-.31)	22.5	(.89)	25	Gray	20013.0
PG16	6.5-9.5	(.26-.37)	22.5	(.89)	25	Black	20014.0
PG16	7.0-10.5	(.28-.41)	22.5	(.89)	25	Green	20015.0
PG16	9.0-13.0	(.35-.51)	22.5	(.89)	25	Red	20016.0
PG16	11.5-15.5	(.45-.61)	22.5	(.89)	25	White	20017.0
PG21	7.0-10.5	(.28-.41)	28.5	(1.12)	25	Green	20018.0
PG21	9.0-13.0	(.35-.51)	28.5	(1.12)	25	Red	20019.0
PG21	11.5-15.5	(.45-.61)	28.5	(1.12)	25	White	20020.0
PG21	14.0-18.0	(.55-.71)	28.5	(1.12)	25	Blue	20021.0
PG21	17.0-20.5	(.67-.81)	28.5	(1.12)	25	Brown	20022.0
PG29	11.5-15.5	(.45-.61)	37.0	(1.46)	20	White	20023.0
PG29	14.0-18.0	(.55-.71)	37.0	(1.46)	20	Blue	20024.0
PG29	17.0-20.5	(.67-.81)	37.0	(1.46)	20	Brown	20025.0
PG29	20.0-25.0	(.79-.98)	37.0	(1.46)	20	Orange	20026.0
PG29	24.0-28.0	(.94-1.10)	37.0	(1.46)	20	Light Yellow	20027.0
PG36	27.0-32.0	(1.06-1.26)	47.0	(1.85)	10	Dark Gray	20028.0
PG36	29.0-34.0	(1.14-1.34)	47.0	(1.85)	10	Light Blue	20029.0
PG36	32.0-36.0	(1.26-1.42)	47.0	(1.85)	10	Rose	20030.0
PG42*	36.0-40.0	(1.42-1.57)	54.0	(2.13)	5	White	20031.0
PG48*	39.0-44.0	(1.54-1.73)	59.5	(2.34)	5	White	20032.0

\*Body Material POM Temperature Range: -40 to 110°C (-40 to 230°F)