

Straight Through – PG External Thread Polyvinylidene (PVDF)



- Protection Rating: IP68; NEMA 4X
- Pressure Rating: 10Bar; 140psi
- Selection of 2 Insert Materials
- Order Seal Rings and Locknuts Separately
- Optional Centellen High/Low Temperature Seal Rings See Page 301
- Standard Colors: Opaque or Black

Polyvinylidene (PVDF)



With Thermoplastic Elastomer (TPE)
Tubular Sealing Insert

Material Specifications	
Body	Polyvinylidene (PVDF)
Insert	Thermoplastic Elastomer (TPE)
Temperature Range	
Body	-40 to 150°C (-40 to 302°F)
Insert	-40 to 130°C (-40 to 266°F)
Insert Color	Various

Size	Cable Dia.		Mtg. Hole Dia.		Std. Pk.	Sealing Insert Color	Cat. No.	
	mm	(in.)	mm	(in.)			Opaque	Black
PG7	4.0-6.5	(.16-.26)	12.5	(.49)	50	Yellow	20075.4	20110.5
PG9	4.0-6.5	(.16-.26)	15.2	(.60)	50	Yellow	20076.4	20111.5
PG9	5.0-8.0	(.20-.31)	15.2	(.60)	50	Gray	20077.4	20112.5
PG9	6.5-9.5	(.26-.37)	15.2	(.60)	50	Black	20078.4	20113.5
PG11	4.0-6.5	(.16-.26)	18.5	(.73)	50	Yellow	20079.4	20114.5
PG11	5.0-8.0	(.20-.31)	18.5	(.73)	50	Gray	20080.4	20115.5
PG11	6.5-9.5	(.26-.37)	18.5	(.73)	50	Black	20081.4	20116.5
PG11	7.0-10.5	(.28-.41)	18.5	(.73)	50	Green	20082.4	20117.5
PG13.5	4.0-6.5	(.16-.26)	20.5	(.81)	50	Yellow	20083.4	20118.5
PG13.5	5.0-8.0	(.20-.31)	20.5	(.81)	50	Gray	20084.4	20119.5
PG13.5	6.5-9.5	(.26-.37)	20.5	(.81)	50	Black	20085.4	20120.5
PG13.5	7.0-10.5	(.28-.41)	20.5	(.81)	50	Green	20086.4	20121.5
PG13.5	9.0-13.0	(.35-.51)	20.5	(.81)	50	Red	20087.4	20122.5
PG16	4.0-6.5	(.16-.26)	22.5	(.89)	25	Yellow	20088.4	20123.5
PG16	5.0-8.0	(.20-.31)	22.5	(.89)	25	Gray	20089.4	20124.5
PG16	6.5-9.5	(.26-.37)	22.5	(.89)	25	Black	20090.4	20125.5
PG16	7.0-10.5	(.28-.41)	22.5	(.89)	25	Green	20091.4	20126.5
PG16	9.0-13.0	(.35-.51)	22.5	(.89)	25	Red	20092.4	20127.5
PG16	11.5-15.5	(.45-.61)	22.5	(.89)	25	White	20093.4	20128.5
PG21	7.0-10.5	(.28-.41)	28.5	(1.12)	25	Green	20094.4	20129.5
PG21	9.0-13.0	(.35-.51)	28.5	(1.12)	25	Red	20095.4	20130.5
PG21	11.5-15.5	(.45-.61)	28.5	(1.12)	25	White	20096.4	20131.5
PG21	14.0-18.0	(.55-.71)	28.5	(1.12)	25	Blue	20097.4	20132.5
PG21	17.0-20.5	(.67-.81)	28.5	(1.12)	25	Brown	20098.4	20133.5
PG29	11.5-15.5	(.45-.61)	37.0	(1.46)	20	White	20099.4	20134.5
PG29	14.0-18.0	(.55-.71)	37.0	(1.46)	20	Blue	20100.4	20135.5
PG29	17.0-20.5	(.67-.81)	37.0	(1.46)	20	Brown	20101.4	20136.5
PG29	20.0-25.0	(.79-.98)	37.0	(1.46)	20	Orange	20102.4	20137.5
PG29	24.0-28.0	(.94-1.10)	37.0	(1.46)	20	Light Yellow	20103.4	20138.5
PG36	27.0-32.0	(1.06-1.26)	47.0	(1.85)	10	Dark Gray	20104.4	20139.5
PG36	29.0-34.0	(1.14-1.34)	47.0	(1.85)	10	Light Blue	20105.4	20140.5
PG36	32.0-36.0	(1.26-1.42)	47.0	(1.85)	10	Rose	20106.4	20141.5