

## Multi-Cable Solid Insert - PG External Thread

- Protection Rating: IP68; NEMA 4X  
If Cable Diameter = Insert Hole Diameter
- Protection Rating: IP65; NEMA 3 If Cable Diameter is up to 10% less than Insert Hole Diameter
- Perbunan Seal Rings Factory Installed on Nickel Plated Brass Cord Grips
- Silicone Seal Rings Factory Installed on Stainless Steel Cord Grips
- Order Seal Rings Separately for Polyamide & Polyvinylidene Cord Grips
- Order Locknuts Separately for all Multi-Cable Cord Grips
- Standard Colors: Beige, Black or Opaque

Polyamide (PA)  
Beige



Polyamide (PA)  
Black



With Thermoplastic Elastomer (TPE)  
Multi-Cable Insert

Size	Hole Insert	Std. Pk.
PG7	Solid	50
PG9	Solid	50
PG11	Solid	50
PG13.5	Solid	50
PG16	Solid	25
PG21	Solid	10
PG29	Solid	5
PG36	Solid	5
PG42	Solid	5
PG48	Solid	5

Cat. No.  
Beige

20920.0  
20921.0  
20922.0  
20923.0  
20924.0  
20925.0  
20926.0  
20927.0  
-  
-

Cat. No.  
Black

20920.1  
20921.1  
20922.1  
20923.1  
20924.1  
20925.1  
20926.1  
20927.1  
-  
-

## Solid Insert Worksheet

### Shop Drilling:

- Place Cord Grip with installed insert into vise
- Drill holes at a maximum of 800rpm
- Do not exceed a tolerance of 1.0mm (.039in.)
- Minimum clearance between holes 1.0mm (.039in.)

