

Adapters - PG to NPT

PG to NPT



Material Specifications	Nickel Plated Brass (NPB)
Temperature Range	-40 to 300°C (-40 to 572°F)
Seal Rings	Order Separately (See Page 300)

PG to NPT

External Thread DA	Internal Thread DI	Cat. No.	Dimensions: mm (in.)					Std. Pk.
			A	B	C	E	F	
PG11	NPT3/8"	22890.9	20.0 (.79)	14.5 (.57)	5.5 (.22)	20.0 (.79)	13.0 (.51)	100
PG11	NPT1/2"	22891.9	24.5 (.96)	18.0 (.71)	6.5 (.26)	24.0 (.94)	15.0 (.59)	100
PG13.5	NPT1/2"	22892.9	24.5 (.96)	18.0 (.71)	6.0 (.24)	24.0 (.94)	15.0 (.59)	100
PG16	NPT1/2"	22893.9	24.5 (.96)	18.0 (.71)	6.0 (.24)	24.0 (.94)	15.0 (.59)	100
PG21	NPT3/4"	22894.9	25.0 (.98)	18.0 (.71)	6.5 (.26)	25.0 (.98)	15.0 (.59)	100
PG29	NPT1"	22895.9	26.0 (1.02)	18.0 (.71)	7.5 (.30)	39.0 (1.54)	15.0 (.59)	25
PG36	NPT1-1/4"	22896.9	29.0 (1.14)	20.0 (.79)	8.5 (.33)	50.0 (1.97)	15.0 (.59)	10
PG42	NPT1-1/2"	22897.9	28.0 (1.10)	18.0 (.71)	9.5 (.37)	57.0 (2.24)	17.0 (.67)	10

