










**DIN rails TS | DIN rail brackets TSTW/TST**

DIN rails TS 15		TS 15	TS 15	TS 15
<p>The design of the <b>TS</b> DIN rail complies with the European norm DIN EN 60715. The steel DIN rail is galvanized and has a coating of blue chromate that is at least 10 µm thick. We place extra importance on maintaining a high degree of dimensional accuracy. The steel DIN rails can be used as protective-earth busbars (with PE function) in compliance with DIN VDE 0611 part 3. Please note the following when using the rail as a PEN busbar:</p> <ul style="list-style-type: none"> <li>• Only one E-Cu rail should be used.</li> <li>• The short-circuit currents and the rated thermal currents must be observed.</li> </ul> <p>The DIN rails are delivered in standard lengths of 2 meters. All DIN rails are also available in prepared (cut to length) versions, but all types are available pre-cut to customers requirements.</p>				
				
				
Type		Qty.		Qty.
Type	TS 15 unslotted		TS 15 slotted	
Cat. no.	<b>2091.0</b>	2m	<b>2092.0</b>	2m
Type/colour				
Cat. no.				
Features				
Material	Steel		Steel	Aluminium
Processing	unslotted		slotted 4.2 x 12	unslotted

DIN rail brackets TSTW/TST		TSTW/M6	TSTW/M6	TSTW/F/M6
				
		DIN rail bracket M6	DIN rail bracket M5	DIN rail bracket M6
Type		Qty.		Qty.
Type	TSTW/M6		TSTW/M6	
Cat. no.	<b>2303.0</b>	10	<b>2414.0</b>	10
Type/colour				
Cat. no.				
Features				
Material	Steel		Steel	Steel
Drill hole	M 6		M 5	M 6
Height, mm	48		48	32
Accessories		Qty.		Qty.
Screw	BS M 6x12/15		BS M 5x8/15	
Cat. no.	<b>2304.0</b>	50	<b>2415.0</b>	50