

## Double-level terminals with electronic components RKD



### Screw connection system



- Foot can be snapped on TS 32 and TS 35 DIN rails
- Housing made from polyamide 6.6 UL 94-V2



### Connection diagram

#### RKD 4/D6





Double-level terminals with electronic components

#### RKD 4/D5



Double-level terminals with electronic components

#### RKD 4/D3



Double-level terminals with electronic components

### Connection type

Size (L x W x H) mm with TS 32 mm

Size (L x W x H) mm with TS 35 x 7.5 mm

### Type

Type colour

Cat. no.

Type colour

Cat. no.

Type colour

Cat. no.

Type colour

Cat. no.

Type/colour

Cat. no.

Colours available

### Rated specifications acc. to

Rated voltage, V

Rated current, A

Diode reverse voltage, V

Diode current, A

Diode type

Resistance

Rated wire cross-section, mm<sup>2</sup> | AWG

Plug gauge acc. to EN 60 947-1 | Flamm. class acc. to UL 94

### Connection data

Single wire (solid) / Stranded mm<sup>2</sup>

Stranded/stranded (w/ferrules acc. to DIN 46 228/1) mm<sup>2</sup>

Contact wire range, mm<sup>2</sup>

Stripping length, mm

Torque, Nm | Screw

Special connection, mm

### Features

Material of insulated housing | Temperature range

Number of cross-connection channels | Test pick-off

### Accessories

End plate AP

Cat. no.

Insulation plate TRS

Cat. no.

Socket plug STB

Cat. no.

Test plug PS

Cat. no.

Cross-connector Q

Cat. no.

Cross-connector Q

Cat. no.

Cross-connector Q

Cat. no.

Cross-connector Q

Cat. no.

End stop ES

Cat. no.

Screwdriver SDB

Cat. no.

Quick marking PMC SB

Cat. no.

### Screw connection

60.2 x 6 x 65.5

60.2 x 6 x 61

RKD 4/D6 BG

**2320.2**

100

### Screw connection

60.2 x 6 x 65.5

60.2 x 6 x 61

RKD 4/D5 BG

**2321.2**

100

### Screw connection

60.2 x 6 x 65.5

60.2 x 6 x 61

RKD 4/D3 BG

**2322.2**

100

	Page	Qty.	Page	Qty.	Page	Qty.
AP 4 BG	278	20	278	20	278	20
<b>2101.2</b>					<b>2101.2</b>	
TRS 3 BG	316	100	316	100	316	100
<b>2566.2</b>			<b>2566.2</b>		<b>2566.2</b>	
STB 8.5/2.3	317	50	317	50	317	50
<b>2075.0</b>			<b>2075.0</b>		<b>2075.0</b>	
PS 2,3	317	20	317	20	317	20
<b>2007.0</b>			<b>2007.0</b>		<b>2007.0</b>	
Q 2	289	50	289	50	289	50
<b>2087.0</b>			<b>2087.0</b>		<b>2087.0</b>	
Q 3	289	50	289	50	289	50
<b>2088.0</b>			<b>2088.0</b>		<b>2088.0</b>	
Q 4	288	20	288	20	288	20
<b>2089.0</b>			<b>2089.0</b>		<b>2089.0</b>	
Q 10	289	10	289	10	289	10
<b>2090.0</b>			<b>2090.0</b>		<b>2090.0</b>	
ES 35/K/ST BG	274	50	274	50	274	50
<b>2828.0</b>			<b>2828.0</b>		<b>2828.0</b>	
SDB 0.6x3.5	422	1	422	1	422	1
<b>1086.0</b>			<b>1086.0</b>		<b>1086.0</b>	
PMC SB 6/50 WH	340	500	340	500	340	500
<b>4702.7</b>			<b>4702.7</b>		<b>4702.7</b>	