

## Sealing Plugs - For High Performance Multi-Cable Cord Grips

Sealing Plugs are used in Multi-Cable Cord Grips to seal unused Insert Holes.

- Maintain Cord Grip Protection Rating
- Ensure Strain Relief



Material Specifications		Polyvinylidene (PVDF)		
Temperature Range		-40 to 150°C (-40 to 302°F)		
Color		Black		
Size	Cat. No.	Dimensions mm (in.)		Std. Pk.
		Diameter	Length	
BO1	23240.9	3.0 (.12)	25.0 (.98)	100
BO2	23241.9	4.0 (.16)	20.0 (.79)	100
BO3	23242.9	4.0 (.16)	25.0 (.98)	100
BO4	23243.9	5.3 (.21)	25.0 (.98)	100
BO5	23244.9	6.0 (.24)	25.0 (.98)	100
BO6	23245.9	6.4 (.25)	25.0 (.98)	100
BO7	23246.9	7.0 (.28)	25.0 (.98)	100
BO8	23247.9	7.5 (.30)	25.0 (.98)	100
BO9	23248.9	8.0 (.31)	25.0 (.98)	100
BO10	23249.9	9.3 (.37)	20.0 (.79)	100
BO11	23250.9	10.0 (.39)	20.0 (.79)	100
BO12	23251.9	12.0 (.47)	25.0 (.98)	100
BO13	23252.9	13.0 (.51)	25.0 (.98)	100
BO14	23254.9	5.0 (.20)	25.0 (.98)	100
BO15	23253.9	9.0 (.35)	20.0 (.79)	100
BO16	23255.9	11.0 (.43)	20.0 (.79)	100

## For Standard Multi-Cable Cord Grips

- Maintain Cord Grip Protection Rating
- Ensure Strain Relief



Material Specifications		Polyamide (PA)		
Temperature Range		-20 to 100°C (-4 to 212°F)		
Color		Red		
Size	Cat. No.	Dimensions mm (in.)		Std. Pk.
		Diameter	Length	
MFV5.5	26430.9	5.5 (.22)	20.0 (.79)	50
MFV7	26431.9	7.0 (.28)	20.0 (.79)	50
MFV8	26432.9	8.0 (.31)	23.0 (.91)	50
MFV10	26433.9	10.0 (.40)	27.0 (1.06)	50
MFV12	26434.9	12.0 (.47)	32.0 (1.26)	50
MFV14	26435.9	14.0 (.55)	32.0 (1.26)	50
MFV17	26436.9	17.0 (.67)	35.0 (1.38)	25
MFV21	26437.9	21.0 (.83)	38.0 (1.50)	25