

Straight Through – Metric External Thread

Nickel Plated Brass (NPB)

with Thermoplastic Elastomer (TPE) Insert



- Protection Rating: IP68; NEMA 4X
- Pressure Rating: 10Bar; 140psi
- Neoprene Seal Rings
Factory Installed
- Order Optional High Temperature
Silicone Seal Rings Separately
- Order Locknuts Separately

Nickel Plated Brass (NPB)



With Thermoplastic Elastomer (TPE) Tubular Sealing Insert

Material Specifications	
Body	Nickel Plated Brass (NPB)
Insert	Thermoplastic Elastomer (TPE)
Seal Ring	Neoprene (NBR)
Temperature Range	
Body	-40 to 300°C (-40 to 572°F)
Insert	-40 to 130°C (-40 to 266°F)
Seal Ring	-20 to 100°C (-4 to 212°F)
Insert Color	Various

Size	Cable Dia.		Mtg. Hole Dia.		Std. Pk.	Sealing Insert Color	Cat. No.
	mm	(in.)	mm	(in.)			
M6x.75	2.5-3.0	(.10-.12)	6.0	(.24)	50	White	25431.6
M8x1.0	3.0-4.5	(.12-.18)	8.0	(.31)	50	White	26900.6
M10x1.0	2.0-3.0	(.08-.18)	10.0	(.39)	50	White	26901.6
M10x1.0	2.5-4.0	(.10-.16)	10.0	(.39)	50	White	26902.6
M10x1.0	3.5-5.0	(.14-.20)	10.0	(.39)	50	White	26903.6
M10x1.0	4.0-6.5	(.16-.26)	10.0	(.39)	50	Yellow	26904.6
M10x1.5	2.0-3.0	(.08-.18)	10.0	(.39)	50	White	26911.6
M10x1.5	2.5-4.0	(.10-.16)	10.0	(.39)	50	White	26912.6
M10x1.5	3.5-5.0	(.14-.20)	10.0	(.39)	50	White	26913.6
M10x1.5	4.0-6.5	(.16-.26)	10.0	(.39)	50	Yellow	25400.6
M12x1.5	4.0-6.5	(.16-.26)	12.0	(.47)	50	Yellow	25401.6
M16x1.5	4.0-6.5	(.16-.26)	16.0	(.63)	50	Yellow	25402.6
M16x1.5	5.0-8.0	(.20-.31)	16.0	(.63)	50	Gray	25403.6
M16x1.5	6.5-9.5	(.26-.37)	16.0	(.63)	50	Black	25404.6
M20x1.5	4.0-6.5	(.16-.26)	20.0	(.79)	50	Yellow	25405.6
M20x1.5	5.0-8.0	(.20-.31)	20.0	(.79)	50	Gray	25406.6
M20x1.5	6.5-9.5	(.26-.37)	20.0	(.79)	50	Black	25407.6
M20x1.5	7.0-10.5	(.28-.41)	20.0	(.79)	50	Green	25408.6
M20x1.5	9.0-13.0	(.35-.51)	20.0	(.79)	50	Red	25409.6
M25x1.5	4.0-6.5	(.16-.26)	25.0	(.98)	50	Yellow	25410.6
M25x1.5	5.0-8.0	(.20-.31)	25.0	(.98)	50	Gray	25411.6
M25x1.5	6.5-9.5	(.26-.37)	25.0	(.98)	50	Black	25412.6
M25x1.5	7.0-10.5	(.28-.41)	25.0	(.98)	50	Green	25413.6
M25x1.5	9.0-13.0	(.35-.51)	25.0	(.98)	50	Red	25414.6
M25x1.5	11.5-15.5	(.45-.61)	25.0	(.98)	50	White	25415.6
M32x1.5	7.0-10.5	(.28-.41)	32.0	(1.26)	25	Green	25416.6
M32x1.5	9.0-13.0	(.35-.51)	32.0	(1.26)	25	Red	25417.6
M32x1.5	11.5-15.5	(.45-.61)	32.0	(1.26)	25	White	25418.6
M32x1.5	14.0-18.0	(.55-.71)	32.0	(1.26)	25	Blue	25419.6
M32x1.5	17.0-20.5	(.67-.81)	32.0	(1.26)	25	Brown	25420.6
M40x1.5	11.5-15.5	(.45-.61)	40.0	(1.57)	10	White	25421.6
M40x1.5	14.0-18.0	(.55-.71)	40.0	(1.57)	10	Blue	25422.6
M40x1.5	17.0-20.5	(.67-.81)	40.0	(1.57)	10	Brown	25423.6
M40x1.5	20.0-25.0	(.79-.98)	40.0	(1.57)	10	Orange	25424.6
M40x1.5	24.0-28.0	(.94-1.10)	40.0	(1.57)	10	Light Yellow	25425.6
M50x1.5	27.0-32.0	(1.06-1.26)	50.0	(1.97)	5	White	25426.6
M50x1.5	29.0-34.0	(1.14-1.34)	50.0	(1.97)	5	Light Blue	25427.6
M50x1.5	32.0-36.0	(1.26-1.42)	50.0	(1.97)	5	Rose	25428.6
M50x1.5	36.0-40.0	(1.42-1.57)	50.0	(1.97)	5	White	25429.6

Continued on page 24.