






Seals	black small			
	Type	Cat. no.	Qty.	Max. Ø
	KDS-DE/B BK	28520.4	10	Blind
	KDS-DE 1.5-2 BK	28521.4	10	2 mm
	KDS-DE 2-3 BK	28522.4	10	3 mm
	KDS-DE 3-4 BK	28523.4	10	4 mm
	KDS-DE 4-5 BK	28524.4	10	5 mm
	KDS-DE 5-6 BK	28525.4	10	6 mm
	KDS-DE 6-7 BK	28526.4	10	7 mm
	KDS-DE 7-8 BK	28527.4	10	8 mm
	KDS-DE 8-9 BK	28528.4	10	9 mm
	KDS-DE 9-10 BK	28529.4	10	10 mm
	KDS-DE 10-11 BK	28530.4	10	11 mm
	KDS-DE 11-12 BK	28531.4	10	12 mm
	KDS-DE 12-13 BK	28532.4	10	13 mm
	KDS-DE 13-14 BK	28533.4	10	14 mm
	KDS-DE 14-15 BK	28608.4	10	15 mm
KDS-DE 15-16 BK	28670.4	10	16 mm	


Seals	black large			
	KDS-DEG/B BK	28534.4	10	Blind
	KDS-DEG 14-15 BK	28535.4	10	15 mm
	KDS-DEG 15-16 BK	28536.4	10	16 mm
	KDS-DEG 16-17 BK	28537.4	10	17 mm
	KDS-DEG 17-18 BK	28538.4	10	18 mm
	KDS-DEG 18-19 BK	28539.4	10	19 mm
	KDS-DEG 19-20 BK	28540.4	10	20 mm
	KDS-DEG 20-21 BK	28541.4	10	21 mm
	KDS-DEG 21-22 BK	28542.4	10	22 mm
	KDS-DEG 22-23 BK	28543.4	10	23 mm
	KDS-DEG 23-24 BK	28544.4	10	24 mm
	KDS-DEG 24-25 BK	28545.4	10	25 mm
	KDS-DEG 25-26 BK	28546.4	10	26 mm
	KDS-DEG 26-27 BK	28547.4	10	27 mm
	KDS-DEG 27-28 BK	28548.4	10	28 mm
	KDS-DEG 28-29 BK	28549.4	10	29 mm
	KDS-DEG 29-30 BK	28550.4	10	30 mm
	KDS-DEG 30-31 BK	28551.4	10	31 mm
KDS-DEG 31-32 BK	28552.4	10	32 mm	
KDS-DEG 32-33 BK	28601.4	10	33 mm	

Seals with multiple holes	black			
	KDS-DE 2 x 4-5 BK	28555.4	10	5 mm
	KDS-DE 2 x 5-6 BK	28556.4	10	6 mm
	KDS-DE 2 x 6.5 BK	28682.4	10	6.5 mm
	KDS-DE 4 x 2-3 BK	28557.4	10	3 mm
	KDS-DE 4 x 3-4 BK	28558.4	10	4 mm
	KDS-DE 4 x 4.5 BK	28681.4	10	4.5 mm
	KDS-DE 4 x 5 BK	28672.4	10	5 mm

Seals for AS interface cables	black			
	KDS-DE/1 x ASI BK	28559.4	10	
	KDS-DE/2 x ASI BK	28560.4	10	

Cone-shaped seals	black			
	KDS-DE/K 2-11 BK	28553.4	10	11 mm
	KDS-DEG/K 7-24 BK	28554.4	10	24 mm

	IP66	NEMA TYPE 12	NEMA TYPE 4X
ECOLAB certified	RoHS compliant	Made in Germany	



Features

- Material: TPE
- Flammability: UL94 HB
- Temperature range: -40 °C to +120 °C (static)
- Halogen-free, silicone-free
- High chemical resistance
- UV-stabilized
- Protection: IP66