

Sealing elements for all KDS systems

Seals	grey small		
	Type	Cat. no.	Qty. Max. Ø
	KDS-DE/B GR	28561.6	10 Blind
	KDS-DE 1.5-2 GR	28562.6	10 2 mm
	KDS-DE 2-3 GR	28563.6	10 3 mm
	KDS-DE 3-4 GR	28564.6	10 4 mm
	KDS-DE 4-5 GR	28565.6	10 5 mm
	KDS-DE 5-6 GR	28566.6	10 6 mm
	KDS-DE 6-7 GR	28567.6	10 7 mm
	KDS-DE 7-8 GR	28568.6	10 8 mm
	KDS-DE 8-9 GR	28569.6	10 9 mm
	KDS-DE 9-10 GR	28570.6	10 10 mm
	KDS-DE 10-11 GR	28571.6	10 11 mm
	KDS-DE 11-12 GR	28572.6	10 12 mm
	KDS-DE 12-13 GR	28573.6	10 13 mm
	KDS-DE 13-14 GR	28574.6	10 14 mm
	KDS-DE 14-15 GR	28609.6	10 15 mm
	KDS-DE 15-16 GR	28671.6	10 16 mm
Seals	grey large		
	KDS-DEG/B GR	28575.6	10 Blind
	KDS-DEG 14-15 GR	28576.6	10 15 mm
	KDS-DEG 15-16 GR	28577.6	10 16 mm
	KDS-DEG 16-17 GR	28578.6	10 17 mm
	KDS-DEG 17-18 GR	28579.6	10 18 mm
	KDS-DEG 18-19 GR	28580.6	10 19 mm
	KDS-DEG 19-20 GR	28581.6	10 20 mm
	KDS-DEG 20-21 GR	28582.6	10 21 mm
	KDS-DEG 21-22 GR	28583.6	10 22 mm
	KDS-DEG 22-23 GR	28584.6	10 23 mm
	KDS-DEG 23-24 GR	28585.6	10 24 mm
	KDS-DEG 24-25 GR	28586.6	10 25 mm
	KDS-DEG 25-26 GR	28587.6	10 26 mm
	KDS-DEG 26-27 GR	28588.6	10 27 mm
	KDS-DEG 27-28 GR	28589.6	10 28 mm
	KDS-DEG 28-29 GR	28590.6	10 29 mm
	KDS-DEG 29-30 GR	28591.6	10 30 mm
KDS-DEG 30-31 GR	28592.6	10 31 mm	
KDS-DEG 31-32 GR	28593.6	10 32 mm	
KDS-DEG 32-33 GR	28594.6	10 33 mm	
Seals with multiple holes	grey		
	KDS-DE 2 x 4-5 GR	28595.6	10 5 mm
	KDS-DE 2 x 5-6 GR	28596.6	10 6 mm
	KDS-DE 2 x 6.5 GR	28607.6	10 6.5 mm
	KDS-DE 4 x 2-3 GR	28597.6	10 3 mm
	KDS-DE 4 x 3-4 GR	28598.6	10 4 mm
	KDS-DE 4 x 4.5 GR	28606.6	10 4.5 mm
	KDS-DE 4 x 5 GR	28673.6	10 5 mm
Seals for AS interface cables	grey		
	KDS-DE/1 x ASI GR	28599.6	10
	KDS-DE/2 x ASI GR	28600.6	10

	IP66	NEMA TYPE 12	NEMA TYPE 4X
	RoHS compliant	Made in Germany	



Features

- Material: TPE
- Flammability: UL 94 V-0
- Temperature range: -40 °C to +90 °C (static)
- Halogen-free, silicone-free
- Protection: IP66