


| Separable cable glands  |      | KDS-KV M40  | KDS-KV M50  | KDS-KV M63  |
|---|------|---|---|---|
|  |      |    |    |    |
| Diagram   |      |    |     |    |
| Type  |      | KDS-KV M40 BK   | KDS-KV M50 BK   | KDS-KV M63 BK   |
| Cat. no.  | Qty. | 28613.4 5   | 28614.4 5   | 28615.4 5   |
| Description   |      | Separable cable gland, including separable locknut                                  | Separable cable gland, including separable locknut                                    | Separable cable gland, including separable locknut                                    |
| Cable diameter, mm  |      | 14-33   | 14-33   | 14-33   |
| Accessories   |      |   |   |   |
| Locknut   |      | KDS-GM 40 BK  | KDS-GM 50 BK  | KDS-GM 63 BK  |
| Cat. no.  | Qty. | 28619.4 5   | 28620.4 5   | 28621.4 5   |
| Description   |      | Separable locknut   | Separable locknut   | Separable locknut   |
| Seals   |      |   |   |   |
| small   |      | KDS-DEG   | KDS-DEG   | KDS-DEG   |
| Cat. no.  | Qty. | Page 42/43  | Page 42/43  | Page 42/43  |
| Tightening torque of lock nut, in Nm  |      | 7   | 7   | 7   |
| Combinations  |      |  |  |  |



## Features

- Material: polyamide PA 6.6, glass-fibre reinforced | TPE
- Colour: black
- Flammability: UL 94 V-0
- Temperature range: -40 °C to +120 °C
- Halogen-free, silicone-free
- Protection: IP66