

KES 16-1/24		KES 17/24		KES 20/24		KES 21/24		KES 32/24	
									
Page 50		Page 51		Page 51		Page 51		Page 51	
KES 16-1/24 GR ● 10 28633.6		KES 17/24 GR ● 10 28634.6		KES 20/24 GR ● 10 28635.6		KES 21/24 GR ● 10 28636.6		KES 32/24 GR ● 10 28637.6	
KES 16-1/24 BK ● 10 28633.4		KES 17/24 BK ● 10 28634.4		KES 20/24 BK ● 10 28635.4		KES 21/24 BK ● 10 28636.4		KES 32/24 BK ● 10 28637.4	
KES-GB 16-1/24 GR ● 10 28643.6		KES-GB 17/24 GR ● 10 28644.6		KES-GB 20/24 GR ● 10 28645.6		KES-GB 21/24 GR ● 10 28646.6		KES-GB 32/24 GR ● 10 28647.6	
KES-GB 16-1/24 BK ● 10 28643.4		KES-GB 17/24 BK ● 10 28644.4		KES-GB 20/24 BK ● 10 28645.4		KES-GB 21/24 BK ● 10 28646.4		KES-GB 32/24 BK ● 10 28647.4	
KES-R 16-1/24 GR ● 10 28653.6		KES-R 17/24 GR ● 10 28654.6		KES-R 20/24 GR ● 10 28655.6		KES-R 21/24 GR ● 10 28656.6		KES-R 32/24 GR ● 10 28657.6	
KES-R 16-1/24 BK ● 10 28653.4		KES-R 17/24 BK ● 10 28654.4		KES-R 20/24 BK ● 10 28655.4		KES-R 21/24 BK ● 10 28656.4		KES-R 32/24 BK ● 10 28657.4	
2 x 3.2-6.3 9 x 4-7.5 1 x 5.5-10.5 1 x 8-12.5 3 x 12-16.2		4 x 3.2-6.3 2 x 4-7.5 1 x 5.5-10.5 10 x 8-12.5		12 x 3.2-6.3 8 x 5.5-10.5		1 x 3.2-6.3 14 x 4-7.5 4 x 5.5-10.5 2 x 8-12.5		32 x 3.2-6.3	
PA 6.6 GF / elastomer -40 °C to +90 °C IP66 UL 94 V-0		PA 6.6 GF / elastomer -40 °C to +90 °C IP66 UL 94 V-0		PA 6.6 GF / elastomer -40 °C to +90 °C IP66 UL 94 V-0		PA 6.6 GF / elastomer -40 °C to +90 °C IP66 UL 94 V-0		PA 6.6 GF / elastomer -40 °C to +90 °C IP66 UL 94 V-0	
Sheet-metal punch Page 54		Sheet-metal punch Page 54		Sheet-metal punch Page 54		Sheet-metal punch Page 54		Sheet-metal punch Page 54	