

KES cable entries

Cable entries	KES 13/24	KES 14/24	KES 16/24
			
Diagram	Page 50	Page 50	Page 50
Mounting type Screw-on mount			
			
Type / colour	KES 13/24 GR ●	KES 14/24 GR ●	KES 16/24 GR ●
<i>Cat. no.</i>	28630.6	28631.6	28632.6
Qty.	10	10	10
Type / colour	KES 13/24 BK ●	KES 14/24 BK ●	KES 16/24 BK ●
<i>Cat. no.</i>	28630.4	28631.4	28632.4
Qty.	10	10	10
Mounting type Screw-on mount, with pressed-in threaded bush			
			
Type / colour	KES-GB 13/24 GR ●	KES-GB 14/24 GR ●	KES-GB 16/24 GR ●
<i>Cat. no.</i>	28640.6	28641.6	28642.6
Qty.	10	10	10
Type / colour	KES-GB 13/24 BK ●	KES-GB 14/24 BK ●	KES-GB 16/24 BK ●
<i>Cat. no.</i>	28640.4	28641.4	28642.4
Qty.	10	10	10
Mounting type Tool-free latch-on mount			
			
Type / colour	KES-R 13/24 GR ●	KES-R 14/24 GR ●	KES-R 16/24 GR ●
<i>Cat. no.</i>	28650.6	28651.6	28652.6
Qty.	10	10	10
Type / colour	KES-R 13/24 BK ●	KES-R 14/24 BK ●	KES-R 16/24 BK ●
<i>Cat. no.</i>	28650.4	28651.4	28652.4
Qty.	10	10	10
Connection data			
Number of cables x cable diameter	10 x 3.2–6.3 3 x 16-20.5	5 x 3.2–6.3 2 x 4-7.5 3 x 5.5-10.5 1 x 8-12.5 3 x 12-16.2	8 x 3.2-5.5 6 x 5-8.5 2 x 9.5-14.5
Features			
Material of frame / sealing plate	PA 6.6 GF / elastomer	PA 6.6 GF / elastomer	PA 6.6 GF / elastomer
Temperature range	–40 °C to +90 °C	–40 °C to +90 °C	–40 °C to +90 °C
Protection	IP66	IP66	IP66
Flammability class	UL 94 V-0	UL 94 V-0	UL 94 V-0
Sheet-metal punch	Sheet-metal punch	Sheet-metal punch	Sheet-metal punch
<i>Cat. no.</i>	Page 54	Page 54	Page 54