

Sheet-metal punch BL

Sheet metal punch for the KDSClick, KDS-FP, KDS-FB, KDS-KV and KES cable entry systems. Using the sheet-metal punch, you can produce the desired break-outs, without any chips, in just a few minutes. The built-in punch-hole marking tip can be used to punch-mark the drill points clearly for screw-on attachments. These sheet-metal punches are compatible with all common hydraulic pumps.

Assortment case



Punch, die, draw stud and counter nut in a plastic case

Sheet-metal punch BL		BL KDS-SR 1-4	BL KDS-SR 6/10	BL KDS-SR 8/16
Type		BL KDS-SR 1-4	BL KDS-SR 6/10	BL KDS-SR 8/16
Cat. no.	Qty.	28674.0	28675.0	28676.0
Maximum wall thickness		2.0 mm, for S 235 sheet metal	2.0 mm, for S 235 sheet metal	2.0 mm, for S 235 sheet metal
Dimensions of break-out hole		46 x 46 mm	83 x 46 mm	103 x 46 mm
Scope of delivery		Punch, die, draw stud, counter nut, plastic case	Punch, die, draw stud, counter nut, plastic case	Punch, die, draw stud, counter nut, plastic case

Sheet-metal punch BL		BL-VA KDS-SR 1-4	BL-VA KDS-SR 6/10	BL-VA KDS-SR 8/16
Type		BL-VA KDS-SR 1-4	BL-VA KDS-SR 6/10	BL-VA KDS-SR 8/16
Cat. no.	Qty.	28683.0	28684.0	28685.0
Maximum wall thickness		2.0 mm, with stainless steel sheet	2.0 mm, with stainless steel sheet	2.0 mm, with stainless steel sheet
Dimensions of break-out hole		46 x 46 mm	83 x 46 mm	103 x 46 mm
Scope of delivery		Punch, die, draw stud, counter nut, plastic case	Punch, die, draw stud, counter nut, plastic case	Punch, die, draw stud, counter nut, plastic case

Sheet-metal punch BL		BL KES	BL KDS-FP2	BL KDS-KV M20
Type		BL KES	BL KDS-FP2	BL KDS-KV M20
Cat. no.	Qty.	28744.0	28745.0	28746.0
Maximum wall thickness		2.0 mm, for S 235 sheet metal	2.0 mm, for S 235 sheet metal	2.0 mm, for S 235 sheet metal
Dimensions of break-out hole		112 x 36 mm	110 x 131 mm	20.4 mm
Scope of delivery		Punch, die, draw stud, counter nut, plastic case	Punch, die, draw stud, counter nut, plastic case	Punch, die

Sheet-metal punch BL		BL-VA KES	BL-VA KDS-FP2	BL-VA KDS-KV M20
Type		BL-VA KES	BL-VA KDS-FP2	BL-VA KDS-KV M20
Cat. no.	Qty.	28752.0	28753.0	28754.0
Maximum wall thickness		2.0 mm, with stainless steel sheet	2.0 mm, with stainless steel sheet	2.0 mm, with stainless steel sheet
Dimensions of break-out hole		112 x 36 mm	110 x 131 mm	20.4 mm
Scope of delivery		Punch, die, draw stud, counter nut, plastic case	Punch, die, draw stud, counter nut, plastic case	Punch, die