

KDS-FB

Cable entry system for flat cables

Frame	KDS-SR-FB1/A	KDS-SR-FB2/A	KDS-SR-FB2/B
			

Diagram	Page 14	Page 14	Page 14
Type / colour	KDS-SR-FB1/A BK	KDS-SR-FB2/A BK	KDS-SR-FB2/B BK
Cat. no.	28700.4	28701.4	28702.4
Qty.	10	10	10
Seals (refer to page 16)			
KDS-DE 20 x 20			1 x
KDS-DE-FB1	1 x		1 x
KDS-DE-FB2		1 x	
KDS-DE-FB3			
KDS-DE-FB4			
Accessories			
Actuating tool (refer to page 40)	KDS BW 1	KDS BW 1	KDS BW 1
Cat. no.	28622.0	28622.0	28622.0
Qty.	1	1	1
Sheet-metal punch (refer to page 54)	BL-VA KDS-FB1	BL-VA KDS-FB2	BL-VA KDS-FB2
Cat. no.	28729.0	28730.0	28730.0
Qty.	1	1	1

Frame	KDS-SR-FB4/A	KDS-SR-FB4/B	KDS-SR-FB4/C
			

Diagram	Page 15	Page 15	Page 15
Type / colour	KDS-SR-FB4/A BK	KDS-SR-FB4/B BK	KDS-SR-FB4/C BK
Cat. no.	28707.4	28708.4	28709.4
Qty.	10	10	10
Seals (refer to page 16)			
KDS-DE 20 x 20		2 x	1 x
KDS-DE-FB1			2 x
KDS-DE-FB2		1 x	
KDS-DE-FB3			
KDS-DE-FB4	1 x		
Accessories			
Actuating tool (refer to page 40)	KDS BW 1	KDS BW 1	KDS BW 1
Cat. no.	28622.0	28622.0	28622.0
Qty.	1	1	1
Sheet-metal punch (refer to page 54)	BL-VA KDS-FB4	BL-VA KDS-FB4	BL-VA KDS-FB4
Cat. no.	28732.0	28732.0	28732.0
Qty.	1	1	1



Features

- Material: polyamide PA 6.6, glass-fibre reinforced | TPE
- Colour: black
- Flammability: UL 94 V-0
- Temperature range: -40 °C to +120 °C
- Halogen-free, silicone-free
- Protection: IP66