











Seals for KDS-FB

Seals	KDS-DE-FB1/A	KDS-DE-FB1/B	KDS-DE-FB1/C	KDS-DE-FB1/D	KDS-DE-FB1/E	KDS-DE-FB1/F	KDS-DE-FB2/A
							
Type / colour	KDS-DE-FB1/A GR	KDS-DE-FB1/B GR	KDS-DE-FB1/C GR	KDS-DE-FB1/D GR	KDS-DE-FB1/E GR	KDS-DE-FB1/F GR	KDS-DE-FB2/A GR
Cat. no.	28713.6	28714.6	28715.6	28716.6	28717.6	28718.6	28719.6
Qty.	5	5	5	5	5	5	5
Sealing area		Width: 19 ... 23 mm Thickness: 5.5 ... 6 mm	Width: 28 ... 33 mm Thickness: 5.5 ... 6 mm	Width: 24 ... 30 mm Thickness: 8.5 ... 9 mm	Width: 19 ... 24 mm Thickness: 6.5 ... 7 mm	Width: 28 ... 33 mm Thickness: 9 ... 9.5 mm	

Seals	KDS-DE-FB2/B	KDS-DE-FB2/C	KDS-DE-FB2/D	KDS-DE-FB2/E	KDS-DE-FB2/F	KDS-DE-FB3/A	KDS-DE-FB3/B
							
Type / colour	KDS-DE-FB2/B GR	KDS-DE-FB2/C GR	KDS-DE-FB2/D GR	KDS-DE-FB2/E GR	KDS-DE-FB2/F GR	KDS-DE-FB3/A GR	KDS-DE-FB3/B GR
Cat. no.	28720.6	28721.6	28722.6	28723.6	28724.6	28725.6	28726.6
Qty.	5	5	5	5	5	5	5
Sealing area	Width: 32.5 ... 38 mm Thickness: 5 ... 5.5 mm	Width: 45 ... 50.5 mm Thickness: 6 ... 6.5 mm	Width: 47 ... 52 mm Thickness: 9.5 ... 10 mm	Width: 38 ... 43 mm Thickness: 12.5 ... 13 mm	Width: 49 ... 54 mm Thickness: 5 ... 6 mm		Width: 72 ... 77 mm Thickness: 5 ... 5.5 mm

Seals	KDS-DE-FB1/A	KDS-DE-FB4/B
		
Type / colour	KDS-DE-FB4/A GR	KDS-DE-FB4/B GR
Cat. no.	28727.6	28728.6
Qty.	5	5
Sealing area		Width: 85 ... 99 mm Thickness: 4.2 ... 5.2 mm



Features

- Material: TPE
- Flammability: UL 94 V-0
- Temperature range: -40 °C to +90 °C (static)
- Halogen-free, silicone-free
- Protection: IP66