



Heavy Duty Circuit Breakers

Type I Cycle or continuously "re-set" until the overload is corrected.

Type II Remain open as long as the overload exists, reset when the situation is corrected. Power must be disconnected for breaker to reset.


Type III Remain open until manually reset by pushing the button.

Type I, Type II and Type III conform to SAE recommended practice J 553C.

Type I – Cycling Circuit Breakers

Plug-in Circuit Breakers

- Universal "plug-in" mounted circuit breakers.
- Heavy duty replacement for ATC and ATO blade fuses.
- Terminals are grooved for easy size adjustment, snap off with pliers.
- Saves time and cost of replacing burnt-out fuses.
- Size: .84" L x .40 W" x 1.50 H" (21.33mm x 10.16mm x 38.10mm).




12 volts, D.C.

Amperes	Part No.
10	30409-10
15	30409-15
20	30409-20
25	30409-25
30	30409-30

Replacement Information

Position A	Ford Pickup Trucks
Position B	Dodge Trucks Ford Trucks (Heavy) Navistar (IHC) Trucks
Position C	Kenworth Trucks

Stud Terminals • Mounting Bracket



- Two #10-32 stud terminals, hex nuts and lock washers supplied.
- Size: 2.0" L x .78" W x 1.37" H (50.80mm x 19.81mm x 34.97mm).
- Two .22" (5.58mm) mounting holes, 1.56" (39.62mm) on center.

24 volts, D.C.

Amperes	Part No.	Amperes	Part No.
10	30172-10	20	30172-20
15	30172-15	30	30172-30

12 volts, D.C.

Amperes	Part No.	Amperes	Part No.
6	30055-6	25	30055-25
8	30055-8	30	30055-30
10	30055-10	40	30055-40
15	30055-15	50	30055-50
20	30055-20		

Stud Terminals



- Two #10-32 stud terminals, hex nuts and lock washers supplied.
- Dimples stamped in case provide secure snap-in bracket mounting (please see pg. 64 for mounting brackets).
- Size: 1.25" L x .78" W x 1.33" H (31.75mm x 19.81mm x 33.78mm).


24 volts, D.C.

Amperes	Part No.	Amperes	Part No.
10	30171-10	20	30171-20
15	30171-15	30	30171-30

12 volts, D.C.

Amperes	Part No.	Amperes	Part No.
6	30056-6	25	30056-25
8	30056-8	30	30056-30
10	30056-10	40	30056-40
15	30056-15	50	30056-50
20	30056-20		

Stud Terminals Cross Wide Mounting Bracket



- Two #10-32 stud terminals with hex nuts and lockwashers.
- Size: 2.0" L x .78" W x 1.37" H (50.80mm x 19.81mm x 34.97mm).

12 volts, D.C.

Amperes	Part No.	Amperes	Part No.
6	30128-6	20	30128-20
8	30128-8	25	30128-25
10	30128-10	30	30128-30
15	30128-15	40	30128-40

Stud & Blade Terminals



- Double blade terminal on one end and a #10-32 stud terminal on the other.
- Dimples stamped in case for secure snap-in mounting (please see pg. 64 for mounting brackets).
- Size: 1.25" L x .78" W x 1.20" H

12 volts, D.C.

Amperes	Part No.
20	30404-20
30	30404-30

⊖ Subject to availability. Special minimum order quantity may apply. Please consult factory.