



# 4 & 5-POLE CONNECTORS

## 4-POLE SOCKET




## 4-POLE PLUG




4-POLE POS	5-POLE POS	Color	Circuits
W	1	White	Ground Return
G	5	Green	Right Turn & Brake Lights
Y/R	3	Yellow or	Left Turn & Brake Lights
	4	Red	
B	2	Brown	Tail Lights

## 5-POLE SOCKET



## 5-POLE PLUG



## 4-POLE CONNECTORS - 12-24 Volts, 35 Amp.

- Zinc Die-Cast 4-pole unit incorporates many new and improved features.
- Extended exterior and socket conceals terminals.
- Unique cable clamp prevents chafing, gives more cable support, and saves installation time.
- Integral finger grips for positive pull, difficult to shake loose.
- Stainless steel spring.
- Dust and water resistant.
- Polarized for proper wiring
- Terminals accept up to #12 gauge wire.
- Two 1/4" diameter mounting holes on 4-pole sockets. 2-7/8" on center. Mounts through 1-3/8" diameter hole.

Interchangeable with competitive brands.

**11-402**  
Plug, no cable guard



**11-404**  
Connector socket

**11-403**  
Plug with cable guard



**11-400**  
Consist of 11-402 Plug and 11-404 Socket.



## 4-POLE CONNECTORS - Chrome Plated, 12-24 Volts, 20 Amp

- Polarized design.
- Chrome Plated Die-Cast Zinc with high impact insulators and split brass contacts.

**11-409**  
Connector Plug



**11-410**  
Connector socket



**11-408**  
Consists of 11-409 Plug and 11-410 Socket

## 5-POLE CONNECTORS - 12-24 Volts, 15 Amps

- Polarized design.
- Chrome plated zinc housing with spring loaded cover.
- Durable interiors.
- Split brass contact for maximum current carrying capacity.
- Mounting holes 1 3/4" diameter on centers.

**11-502**  
Connector socket



**11-500**  
Consist of 11-501 Plug and 11-502 Socket



**11-501**  
Connector plug