

Shrink-Kon® splice insulators and insulating covers

Adhesive insulating covers



- Seals against moisture
- Voltage rating up to 600
- Workable from 14 °F to 120 °F
- Maximum operating temperature of 176 °F
- No installing tools required
- Also available in 10' rolls; consult customer service

Specifications

Electrical

- Dielectric constant: 3.2 ASTM-D150 (60 Hz)
- Power factor: 007 ASTM-D150 (60 Hz)
- Dielectric strength: 340 V/mil ASTM-D1373

Chemical

- Water absorption: 0.06% ASTM-570
- Ozone resistance – Excellent: 03% ASTM-D1373
- Corrosion none visible: per ASTM-D 69

Adhesive insulating covers



Cat. no.	Dimensions (in.)		Std. pkg.
	A	B	
AC 5 x 3	5	3	10
AC 5 x 7	5	7	10
AC 85 x 75	8.5	7.5	5
AC 85 x 105	8.5	10.5	5

Order multiple is std. pkg.

UL listed for use with ABB covers.

For "H" Taps, "C" Taps, two-way connectors, mechanical taps and Color-Keyed® lugs and joints.

Material: 6 mil electrical vinyl backing, butyl rubber mastic adhesive thickness 1/16" approx. Polyethylene release sheet.

UL listed – File No. E9809.

Not for submersion in liquid.

Adhesive insulating covers

Adhesive insulator cat. nos.	Compression														
	Compression lug cat. nos.					Compression two-way connector cat. nos.		"H" tap cat. nos.	"C" tap cat. nos.	Compression cable joints cat. nos.					
AC 5 x 3	60096	60113	60130	60150	54132	54145	54160	54207	54906	54860	60500	54806	63105	54710	54610
size key #2	60097	60114	60132	60151	54134	54108	54162	54208	54942	54862	60501	54807	–	54715	54615
	60099	60116	60134	60230	54105	54147	54163	54255	54947	54864	60507	54806	–	54720	54620
	60101	60117	60135	60236	54135	54148	54111	54209	54909	54866	60512	54504	–	54725	54625
	60102	60118	60136	60238	54136	54150	54165	54210	54910	–	60516	54505	–	54730	54630
	60103	60120	60138	60242	54138	54152	54167	54260	54965	–	60905	54506	–	54735	54635
	60104	60122	60140	60244	54106	54153	54168	54211	54970	–	60910	54507	–	54740	–
	60106	60123	60141	60248	54139	54109	54112	54265	54850	–	60915	54506	–	54745	–
	60107	60124	60142	60250	54140	54155	54170	54212	54852	–	60920	54509	–	54750	–
	60108	60126	60144	54104	54107	54157	54204	54270	54854	–	60925	54510	–	–	–
	60109	60128	60147	54130	54142	54158	54205	54930	54856	–	54804	54511	–	–	–
	60112	60129	60148	54131	54143	54110	54206	54905	54858	–	54805	–	–	–	–

(Continued on next page)