



HILEC Inc.
 11 Railroad Avenue
 Arcade, New York 14009
 Phone: (716) 492-2212
 Fax: (800) 450-8193

HILEC 547R SUPERSTRETCH
EXPANDABLE SILICONE RUBBER COATED FIBERGLASS SLEEVING

THERMAL CLASS: 200°C

MIL-I-3190/6 (Grade A)

NEMA TF-1, Type 5

DESCRIPTION

547R SUPERSTRETCH is comprised of a two-component liquid silicone rubber continuously applied to expandable fiberglass braid. This construction allows the sleeving to be expanded to over twice its relaxed diameter. **547R SUPERSTRETCH** provides superior expandability while retaining excellent physical and electrical properties over a wide range of temperatures (-55°C to +200°C).

RECOMMENDED USE

547 SUPERSTRETCH is recommended for sleeving applications which require a snug fit over irregular shapes. It has the capability to provide a "heat shrink"-like fit while still exhibiting flexibility, abrasion resistance, moisture resistance, cut-through resistance and chemical resistance.

PHYSICAL PROPERTIES (coating)

Hardness	30 durometer, shore A	Ozone	Excellent
Tensile Strength	>1000 psi	Corona	Excellent
Elongation	>600 %	Radiation	Excellent
100% Modulus	300 psi	Sunlight	Excellent
Tear strength	150 pli	Fungus	Excellent
Compression set	>8.0% (22 hrs @ 177°C)		

DIELECTRIC GRADE	PRODUCT NUMBER	MIN. AVE. BREAKDOWN	MIN. INDIV.
A	547RSS	8000	6000

AVAILABILITY

- **SIZES:** **547R SUPERSTRETCH** is available in continuous spooled lengths or cut lengths in NEMA sizes #24 through 1/2".
- **COLORS:** **547R SUPERSTRETCH** is available in black and white. Other colors may be available subject to minimum quantities and/or set-up charges.