


Function times	Load current
4 ± 1 s release delay*	max. 10 A
1 s turn-on delay***	
5 ± 1 s pause time***	

Voltage range: 21 to 30 V, Temperature range: -30 to +70°C, Bracket: Yes


Description	VPE**	Part number
24 V, 6-pole	1	5WG 002 450-121



Function times	Load current
4 ± 1 s release delay*	max. 3.5 A
1 s turn-on delay***	
5 ± 1 s pause time***	

Voltage range: 21.2 to 30 V, Temperature range: -40 to +85°C, Bracket: Yes


Description	VPE**	Part number
24 V, 6-pole	50	5WG 002 450-287



Function times	Load current
4 ± 1 s release delay*	max. 3.5 A
1 s turn-on delay***	
5 ± 1 s pause time***	

Voltage range: 21.2 to 30 V, Temperature range: -40 to +85°C, Bracket: Yes

Description	VPE**	Part number
24 V, 6-pole	1	5WG 002 450-291
24 V, 6-pole	100	5WG 002 450-297



Function times	Load current
4 ± 1 s release delay*	max. 3.5 A
1 s turn-on delay***	
5 ± 1 s pause time***	

Voltage range: 21.2 to 30 V, Temperature range: -40 to +85°C, Bracket: No

Description	VPE**	Part number
24 V, 6-pole	1	5WG 002 450-301
24 V, 6-pole	140	5DW 002 450-307