

Fork terminals

Vinyl-insulated locking forks & non-insulated forks




Vinyl-insulated locking forks – Expanded insulation



Cat. no.	Wire range (AWG)	Max. ins. (in.)	Bolt hole (in.)	Rec. tool	Dimensions (in.)				Stock thick. (in.)
					A	B	C	M	
18RA-6FLX	100 22-16	0.170	#6	ERG4001	0.97	0.25	0.25	0.81	0.02
RA2217-170	1,000 22-16	0.170	#6		0.97	0.25	0.25	0.81	
18RA-8FLX	100 22-16	0.170	#8		0.97	0.29	0.25	0.81	
18RA-10FLX	100 22-16	0.170	#10		0.97	0.29	0.25	0.81	
RA2257-170	1,000 22-16	0.170	#10		0.97	0.29	0.25	0.81	0.03
14RB-6FLX	100 18-14	0.200	#6		0.97	0.31	0.27	0.81	
RB2207-200	1,000 18-14	0.200	#6		0.97	0.31	0.27	0.81	
RB2217-200	1,000 18-14	0.200	#6		0.97	0.29	0.27	0.81	
14RB-8FLX	100 18-14	0.200	#8		0.97	0.31	0.27	0.81	0.04
RB2237-200	1,000 18-14	0.200	#8		0.97	0.31	0.27	0.81	
14RB-10FLX	100 18-14	0.200	#10		0.97	0.31	0.27	0.81	
RB2257-200	1,000 18-14	0.200	#10		0.97	0.31	0.27	0.81	
10RC-6FLX	50 12-10	0.250	#6		1.07	0.31	0.27	0.91	0.04
RC2207-250	500 12-10	0.250	#6		1.07	0.31	0.27	0.91	
10RC-8FLX	50 12-10	0.250	#8		1.10	0.37	0.27	0.91	
10RC-10FLX	50 12-10	0.250	#10		1.10	0.37	0.27	0.91	
RC2227-250	500 12-10	0.250	#10		1.10	0.37	0.27	0.91	0.04
10RC-14FLX	50 12-10	0.250	¼		1.22	0.50	0.32	0.96	

Diagram




Non-insulated forks



Cat. no.	Pkg. qty.	Wire range (AWG)	Bolt hole (in.)	Rec. tool	Dimensions (in.)				Stock thick. (in.)
					A	B	C	M	
A18-6F	100	22-16	#6	ERG4002	0.72	0.25	0.27	0.59	0.02
A116	1,000	22-16	#6		0.72	0.25	0.27	0.59	
A18-8F	100	22-16	#8		0.75	0.31	0.27	0.59	
A114	1,000	22-16	#8		0.75	0.31	0.27	0.59	
A18-10F	100	22-16	#10		0.75	0.31	0.27	0.59	0.03
A115-TB	1,000	22-16	#10		0.75	0.31	0.27	0.59	
B14-6F	100	18-14	#6	ERG4002	0.75	0.31	0.27	0.59	
B64	1,000	18-14	#6	ERG4005	0.75	0.31	0.27	0.59	
B19	1,000	18-14	#6		0.66	0.25	0.13	0.50	0.04
B14-8F	100	18-14	#8		0.75	0.31	0.27	0.59	
B65-TB	1,000	18-14	#8		0.75	0.31	0.27	0.59	
B14-10F	100	18-14	#10		0.75	0.31	0.27	0.59	
B115	1,000	18-14	#10		0.75	0.31	0.27	0.59	0.04
B14-14F	100	18-14	¼		0.90	0.44	0.38	0.68	
C10-6F	50	12-10	#6		0.77	0.31	0.27	0.63	
C133	500	12-10	#6		0.77	0.31	0.27	0.63	
C10-8F	50	12-10	#8		0.82	0.38	0.27	0.63	0.04
C114	500	12-10	#8		0.82	0.38	0.27	0.63	
C10-10F	50	12-10	#10		0.82	0.38	0.27	0.63	
C115	500	12-10	#10		0.82	0.38	0.27	0.63	
C10-14F	50	12-10	¼		0.98	0.50	0.37	0.73	0.04
C116-TB	500	12-10	¼		0.98	0.50	0.37	0.73	

Diagram



For multiple wire combinations per UL® File E9609, see page 14.