

Pilot Lights

Internal honeycomb lens.
Single contact

Lens: $\frac{5}{16}$ " (7.94mm) diameter.

Bezel: satin finish stainless steel, $\frac{3}{4}$ " (19.05mm) diameter.

Bulb: 12V #53 bulb supplied, socket accepts miniature bayonet base bulbs.

Mounting stem: $\frac{1}{2}$ " (12.70mm) diameter, $\frac{3}{8}$ " (9.53mm) long.

Self grounding in
metal panels.

Metal socket.



Lens Color	Part No.
Amber	PL-35-AC
Blue	PL-35-BC
Clear	PL-35-CC
Green	PL-35-GC
Red	PL-35-RC

Insulated.

Plastic socket.



Lens Color	Part No.
Amber	PL-36-AC
Blue	PL-36-BC
Clear	PL-36-CC
Green	PL-36-GC
Red	PL-36-RC

Smooth lens.
Single contact

Lens: $\frac{5}{16}$ " (7.94mm) diameter.

Bezel: chrome plated brass, $\frac{7}{8}$ " (22.22mm) diameter.

Bulb: 12V #53 bulb supplied, socket accepts miniature bayonet base bulbs.

Mounting stem: $\frac{3}{4}$ " (19.05mm) diameter, $1\frac{1}{16}$ " (17.46mm) long.

Self grounding in
metal panels.

Metal socket.



Lens Color	Part No.
Amber	PL-5-AC
Clear	PL-5-CC
Green	PL-5-GC
Red	PL-5-RC

Insulated.

Plastic socket.



Lens Color	Part No.
Amber	PL-6-AC
Blue	PL-6-BC
Green	PL-6-GC
Red	PL-6-RC

Marine Construction Pilot Lights

Smooth lens, insulated.

Single contact • Plastic socket

Lens: $1\frac{7}{32}$ " (13.49mm) diameter.

Bezel: chrome plated brass, $\frac{7}{8}$ " (22.22mm) diameter.

Bulb: 12V #53 bulb supplied, socket accepts miniature bayonet base bulbs.

Mounting stem: $\frac{3}{4}$ " (19.05mm) diameter, $1\frac{1}{16}$ " (26.98mm) long.



Lens Color	Part No.
Amber	M-320-AC
Green	M-320-GC
Red	M-320-RC

Smooth lens, insulated.

Double contact • Brass socket and terminals.

Lens: $1\frac{7}{32}$ " (13.49mm) diameter.

Bezel: chrome plated brass, $1\frac{1}{8}$ " (28.57mm) diameter.

Bulb: 12V #68 bulb supplied, socket accepts double contact bayonet base bulbs.

Mounting stem: $\frac{7}{8}$ " (22.22mm) diameter, $1\frac{1}{8}$ " (28.57mm) long.

Insulator: moisture repellent.



Lens Color	Part No.
Amber	PL-16-AC
Clear	PL-16-CC
Green	PL-16-GC
Red	PL-16-RC

Faceted lens, insulated.

Double contact • Metal socket

Lens: $1\frac{5}{16}$ " (23.81mm) diameter.

Bezel: plated brass, $1\frac{1}{4}$ " (31.75mm) diameter.

Bulb: 12V #68 bulb supplied, socket accepts double contact bayonet base bulbs.

Mounting stem: $\frac{7}{8}$ " (22.22mm) diameter, $1\frac{1}{4}$ " (31.75mm) long.

Sealing: gasket sealed lens.

Insulator: moisture repellent molded phenolic.



Lens Color	Part No.
Amber	M-326-AC
Blue	M-326-BC
Clear	M-326-CC
Green	M-326-GC
Red	M-326-RC

Internal honeycomb lens,
self grounding in metal panels.

Single contact • Plastic socket

Lens: $\frac{5}{8}$ " (15.87mm) diameter.

Bezel: satin finish stainless steel, $\frac{3}{4}$ " (19.05mm) diameter.

Bulb: 12V #53 bulb supplied, socket accepts miniature bayonet base bulbs.

Mounting stem: $\frac{1}{2}$ " (12.70mm) diameter, $\frac{7}{8}$ " (22.22mm) long.

Additional ground wire for mounting in insulated panels.



Lens Color	Part No.
Amber	M-328-AC
Blue	M-328-BC
Clear	M-328-CC
Green	M-328-GC
Red	M-328-RC