

Glo-Lite Neon Indicator Lights

Description and Features

| 6063 Series | | 6073 Series | |
|-------------|--------------|-------------|--------------|
| Flat Face | Conical Face | Flat face | Conical Face |
| | | | |

All dimensions in inches.

The Chicago Miniature Lamp Glo-Lite Indicator Lights are designed for applications requiring a low cost, line voltage, power-on indicator. These indicator lights utilize a high brightness C2A neon lamp providing good visibility and a long life. These indicator lights are constructed with a one-piece body and lens and are available in two face configurations, flat or conical, with or without a chrome bezel.

Specifications

| Part Number: | Description |
|--|---------------------------------|
| 6063-001-534R | Red, Flat Face, No Bezel |
| 6063-001-634R | Red, Conical Face, No Bezel |
| 6073-001-534R | Red, Flat Face, Chrome Bezel |
| 6073-001-634R | Red, Conical Face, Chrome Bezel |
| As special order, these indicator lights are available with white, amber or green lenses | |

| | |
|---------------------------|--|
| Mounting Hole: | .375 for 6063 Series, .500 for 6073 Series |
| Mounting Centers: | .500 for 6063 Series, .688 for 6073 Series |
| Maximum Panel Thickness: | 1.25 for 6063 Series, .078 for 6073 Series |
| Housing/Lens Material: | Nylon |
| Bezel (6073 Series only): | Chrome Plated Brass |
| Wire Leads: | 22 AWG, black 105°C PVC Insulation, stranded |
| Electrical: | 125 Volts AC, Built-in 30K ohm 1/4 Watt resistor |
| Approvals: | UL recognized, CSA certified |

Lake-View Electronics Corp. 1054 Pioneer Rd. Grafton, WI Ph: 262-377-8250 Fax: 262-375-0109

www.lvelectronics.com

Email: sales@lvelectronics.com