



Features

Durable, dependable Instrument Lites are specifically designed for instrument panel illumination where localized light is required. The lamp extends out beyond the panel face. Units are available with fixed or rotatable hood. Black hoods have a highly reflective inner surface for peak light output. Holder mounts from front with a hex nut and lockwasher (supplied).

Applications

Panels, switches, meters, legend plates.

Specifications (900-200 and 900-208)

Mechanical

Mtg. hole: .688" (17.48mm) dia. "D" hole
Panel thickness: .406" (10.31mm) max.

Hardware: Cadmium and cronak plated steel
Terminals: Brass

Electrical

Maximum rating: 120V, 3W
Lamp: Not included—refer to Lamp Catalog #8100 for T 3-1/4 miniature bayonet lamps

Materials and Finishes

Hood: Screw-in, fixed position type. Black aluminum outside, clear anodized inside.

Mounting bushing: Black anodized aluminum

Current carrying parts: nonferrous metal

Ordering Information

Catalog No.	Description
900-200	Fixed hood instrument lite with solder lug terminals
900-208	Fixed hood instrument lite with .250" quick-connect terminal

Optional Features on Special Order

Lexan windows and gaskets for drip-proof application
Screw Terminals
Chrome plating

Specifications (900-006 Series)

Mechanical

Mtg. hole: 1.00" (25.4mm) dia.
Panel thickness: .500" (12.70mm) max.

Electrical

Maximum rating: 250V, 1A, 75W
Lamp: not included—refer to Lamp Catalog #8100 for S-6 automotive lamp or C-7 candelabra screw base

Materials and Finishes

Hood: Rotatable 360 degrees. Chrome plated brass.

Mounting bushing: Nickel plated brass

Hardware: Cadmium and cronak plated steel

Terminals: Brass with brass screws

Ordering Information

Catalog No.	Description
900-006	Rotatable hood instrument lite with screw terminals

Optional Features on Special Order

Double contact bayonet sockets
Solder or quick connect lugs