



DUNBAR Heat Shrinkable Tubing Part Number Cross Reference

| DUNBAR P/N | AMS-DTL-23053/ | Inventory | UL VW-1 | TE/Raychem | Sumitomo | 3M | Canusa | Alpha |
|---|---------------------|--|---------|-----------------------------------|--------------------------|--------------------|---------------------------|---------------------|
| Polyolefin Tubing | | | | | | | | |
| DUNBAR-1605 2:1 Shrink Ratio, Flexible 105°C, 600V Rating UL Rated | | No Stock use 1635F Exceeds all Ratings | Yes | | C2 A4 | | CPX51 | |
| DUNBAR-1625 2:1 Shrink Ratio, Flexible 125°C, 600V Rating UL & CSA Rated | | No Stock use 1635F Exceeds all Ratings | Yes | | F2 F32 F2(Z) | CP-221 | | FIT-221V |
| DUNBAR-1635F 2:1 Shrink Ratio, Flexible 135°C, 600V Rating UL, CSA & AMS-DTL-23053/5 | /5 Class 1, 2, 3 | Spools & 4' Lengths Large Inventory All Colors in Stock | Yes | RNF-100 Versafit | SM12 B2 A2 SM35 | FP-301 FP-301VW | CPX100 PO135 CPX876 | FIT-221 FIT-221B |
| DUNBAR-1635F Y/G 2:1 Shrink Ratio, Flexible 135°C, 600V Rating | /5 Class 1 & 3 | Spools & 4' Lengths | Yes | DCPT | B2(Y/G) | | CPX 201 | FIT-260 |
| DUNBAR-1625LT 2:1 Shrink Ratio, Very Flexible 125°C, 600V Rating UL, CSA, AMS-DTL-23053/5 Low Shrink Temperature | /5 Class 3 | Very Limited Inventory - Available by Order | Yes | Versafit V2 | F5 | VFP-876 | LM 145 | FIT-221LT |
| DUNBAR-1625GT 2:1 Shrink Ratio, Very Flexible 125°C, 150V Rating, Thin Wall UL & CSA Rated | | Spools: Black | Yes | Versafit V4 | F4(TW) | | none | FIT-221-TW |
| DUNBAR-1635S 2:1 Shrink Ratio, Semi-Rigid 135°C, 600V Rating AMS-DTL-23053/6 C 1 | /6 Class 1 & 2 | Spools & 4' Lengths Large Inventory All Colors in Stock | Yes | CRN | B8 D | SR-350 | CHM-140 HM 140 | FIT-295 |
| DUNBAR-3635 3:1 Shrink Ratio, Flexible 135°C, 600V Rating UL, CSA, AMS-DTL-23053/5 | /5 Class 1 & 2 | Spools: Black, White, Clear Red and Yellow | Yes | RNF-3000 | SM23 B2(3X) A2(3X) | SFTW-203 | CPX300 | FIT-321V |
| DUNBAR-3635F - Y/G 3:1 Shrink Ratio, Flexible 135°C, 600V Rating | /5 Class 1 & 3 | No Stock 8 week lead time | Yes | | | | | |
| DUNBAR-4635 4:1 Shrink Ratio, Flexible 135°C, 600V Rating UL, CSA, AMS-DTL-23053/5 | /5 Class 1 & 2 | Spools: Black 4' Lengths: Black Colors available | Yes | RP-4800 | B2(4X) | | none | FIT-421 |
| Specialty Tubing | | | | | | | | |
| DUNBAR-CRFR 2:1 Shrink Ratio 120°C, Rating AMS-DTL-23053/1 | /1 Class 1 & 2 | Spools: Black | Yes | NT-FR NT | R10 | NST | CNP 200 | FIT-600 |
| DUNBAR-1675 2:1 Shrink Ratio 175°C, 600V Rating UL & AMS-DTL-23053/8 | /8 | Spools: Clear/Natural 4' Lengths: Clear/Natural & Black Colors are available | Yes | Kynar RW-175 | K | Kynar | CKN 175 HA 150 | FIT-350 |
| DUNBAR-3675 3:1 Shrink Ratio 175°C, 600V Rating UL & AMS-DTL-23053/8 | /8* | No Stock 8 week lead time * Except - Higher Shrink Ratio | Yes | | | | | |
| DUNBAR-DRET 2:1 Shrink Ratio 120°C, 600V Rating AMS-DTL-23053/16 | /16 | Spools: Black | Yes | DR-25 | R120 | | CDR 625 | none |
| DUNBAR-DR150 2:1 Shrink Ratio 150°C, 600V Rating AMS-DTL-23053/16 | /16 | Spools: Black | Yes | DR-25 | R120 | | CDR 625 | none |
| DUNBAR-FK150 2:1 Shrink Ratio 150°C, 600V Rating AMS-DTL-23053/18 | /18 Class 2 | Spools Only Black & Clear | Yes | RNF-150 (Black) RT-375 (Clear) | none | none | none | none |
| DUNBAR-V200 2:1 Shrink Ratio 200°C, 600V Rating AMS-DTL-23053/13 | /13 | Spools Only Black | Yes | Viton | KH230 SM60 SM3-60 | VTN-200 | Deray VT 220 | |

Please contact Dunbar for information about additional products or specifications.



DUNBAR Heat Shrinkable Tubing Part Number Cross Reference

| DUNBAR P/N | AMS-DTL-23053/ | Inventory | UL VW-1 | TE/Raychem | Sumitomo | 3M | Canusa | Alpha |
|---|----------------|---|----------------------------|-------------------------|---------------------|------------|---|---------|
| Dual-Wall, Polyolefin Tubing (Melttable Adhesive Inner Wall) | | | | | | | | |
| DUNBAR-2690NW 3:2 Shrink Ratio, Flexible 90°C Rating Semi-Rigid | | No Stock 8 week lead time | | | O2 | | | |
| DUNBAR-1625W 2:1 Shrink Ratio, Flexible 125°C, 600V Rating UL, CSA, AMS-DTL-23053/4 | /4 Class 2 | Spools & 4' Lengths: Black Limited Colors | | TAT-125 | O2B2 O2C SM24 | EPS-200 | | FIT-750 |
| DUNBAR-3625WS 3:1 Shrink Ratio, Semi-Rigid 135°C, 600V Rating AMS-DTL-23053/4 | /4 Class 1 | 4' Lengths: Black | Yes (jacket only) | SCL | W5DL | MW | | FIT-300 |
| DUNBAR-3635W 3:1 Shrink Ratio, Flexible 135°C, 600V Rating UL, CSA, AMS-DTL-23053/4 | /4 Class 3 | 4' Lengths: Black, White, Clear Red, Yellow, Blue and Green Spools: Black & Clear, through 1/2" | Yes (jacket only) | ATUM 3:1 DWP-125 | W3B2 W3F2 W3C | EPS-300 | CPA100 CPA300 CPA 100/1 or /3 DROP | FIT-321 |
| DUNBAR-4635W 4:1 Shrink Ratio, Flexible 135°C, 600V Rating UL, CSA, AMS-DTL-23953/4 | /4 Class 3 | No Stock 8 week lead time | Yes (jacket only) | ATUM 4:1 | | EPS-400 | | none |
| DUNBAR-4635WS 4:1 Shrink Ratio, Semi-rigid 135°C, 600V Rating | | 4' Lengths Master Spools and any cut length Standard Spools Black & Clear | Yes (jacket only) | ES-2000 ES-1000 | SA2F | SMS TES | Spicemelt | none |
| DUNBAR-4635WT 4:1 Shrink Ratio, Flexible 135°C Rating, Thin Wall AMS-DTL-23053/4 | /4 Class 3 | 4' Lengths: Black Spools: Black | Yes (jacket only) | ATUM 4:1 | W3B2(4X) | EPS-400 | | |
| DUNBAR-4650WS 4:1 Shrink Ratio, Semi-rigid 150°C, 600V Rating Fully Flame Retardant | | 4' Lengths Master Spools and any cut length Standard Spools Black | Yes (jacket & adhesive) | FL 2500 SCT | none | | CFRA | none |
| Medium & Heavy Wall Tubing | | | | | | | | |
| DUNBAR-CATV 3:1 Shrink Ratio, Flexible Adhesive Lined, Medium Wall 125°C/600V | | 4' Lengths: Black | N/A | TCS SCTV | | CCT | CFTV | |
| DUNBAR-PMWT 3:1 Shrink Ratio, Semi-Rigid Adhesive Lined, Medium Wall 125°C/600V | | 4' Lengths: Black & Red | N/A | RMW SST BSTS | | | CFM | FIT-700 |
| DUNBAR-PMWT-FR 3:1 Shrink Ratio, Semi-Rigid AMS-DTL-23053/15 C1 & C2 ABS & DNV | /15 C1 & C2 | 4' Lengths: Black & Red | N/A | SST-FR BSTS-FR | | MDT | | |
| DUNBAR-PHWT 3:1 Shrink Ratio, Semi-Rigid Adhesive Lined, Heavy Wall 125°C/600V | | 4' Lengths: Black & Red | N/A | RHW SST BSTS | | | CFW | |
| DUNBAR-PHWT-FR 3:1 Shrink Ratio, Semi-Rigid AMS-DTL-23053/15 C1 & C2 ABS & DNV | /15 C1 & C2 | 4' Lengths: Black & Red | N/A | SST-FR BSTS-FR HF | | HDT | FCFW | |
| DUNBAR-BBLV 3:1 Shrink Ratio Adhesive Lined, Medium Wall 125°C / 1kV | | No Stock 8 week lead time | N/A | | | | | |
| DUNBAR-BBHV 3:1 Shrink Ratio Adhesive Lined, Medium Wall 125°C / 25kV | | No Stock 8 week lead time | N/A | | | | | |
| DUNBAR-BBHT 3:1 Shrink Ratio Adhesive Lined, Medium Wall 125°C / 35kV | | No Stock 8 week lead time | N/A | | | | | |
| Non-Shrinkable Polyolefin Tubing | | | | | | | | |
| EIT-600 125°C, 600V UL & CSA Rated | | Very Limited Stock 8 week lead time | Yes | | | | | |