

## Flag terminals

### Non-insulated flags



#### Non-insulated flags



Cat. no.	Pkg. qty.	Wire range (AWG)	Bolt hole (in.)	Rec. tool	Dimensions (in.)				Stock thick. (in.)
					A	B	C	M	
AB14-6A	100	22-14	#6	ERG4004	0.55	0.31	0.22	0.39	0.03
AB51	1,000	22-14	#6		0.55	0.31	0.22	0.39	
AB14-8A	100	22-14	#8		0.55	0.31	0.22	0.39	
AB52	1,000	22-14	#8		0.55	0.31	0.22	0.39	
AB14-10A	100	22-14	#10		0.55	0.31	0.22	0.39	
AB53	1,000	22-14	#10		0.55	0.31	0.22	0.39	
C51	500	12-10	#6		0.66	0.31	0.25	0.48	0.04
C10-8A	50	12-10	#8		0.66	0.31	0.25	0.48	
C52	500	12-10	#8		0.66	0.31	0.25	0.48	
C10-10A	50	12-10	#10		0.66	0.31	0.25	0.48	
C53	500	12-10	#10		0.66	0.31	0.25	0.48	
D236	200	8	#10	WT129	0.83	0.50	0.25	0.59	0.06
D226	200	8	#10		0.90	0.50	0.29	0.64	
D271	200	8	1/4		0.92	0.50	0.33	0.68	
E226	200	6	#10		0.93	0.50	0.29	0.69	0.06
E271	200	6	1/4		0.99	0.50	0.33	0.73	
E272	200	6	5/16		1.05	0.50	0.41	0.81	
F226	200	4	#10		1.07	0.56	0.33	0.80	
F271	200	4	1/4		1.10	0.63	0.33	0.80	0.07
F272	200	4	5/16		1.18	0.63	0.41	0.88	
F273	200	4	3/8		1.20	0.63	0.43	0.90	
G671	100	2	1/4		1.20	0.63	0.33	0.89	0.08
G672	100	2	5/16		1.28	0.63	0.41	0.97	
G673	100	2	3/8		1.32	0.63	0.46	1.02	
H672	50	1/0	5/16	13642M	1.31	0.63	0.41	1.01	0.10
H673	50	1/0	3/8		1.36	0.63	0.46	1.06	
J672	50	2/0	5/16		1.46	0.75	0.41	1.10	0.10
J673	50	2/0	3/8		1.51	0.75	0.46	1.15	
J675	50	2/0	1/2		1.67	0.75	0.55	1.24	
K672	50	3/0	5/16		1.59	0.81	0.41	1.19	0.11
K673	50	3/0	3/8		1.64	0.81	0.46	1.24	
K675	50	3/0	1/2		1.76	0.81	0.55	1.34	
M673	50	250 kcmil	3/8		1.89	1.0	0.46	1.43	0.13
M675	50	250 kcmil	1/2		1.99	1.0	0.55	1.52	

Diagram

