

## Ring terminals

Non-insulated large ring terminals – Brazed seam



Non-insulated large ring terminals – Brazed seam



Cat. no.	Pkg. qty.	Wire range (AWG)	Bolt hole (in.)	Rec. tool	Dimensions (in.)				Stock thick. (in.)	
					A	B	C	M		
D8-10	25	8	#10	TBM6S	1.09	0.42	0.34	0.90	0.06	
D36	200	8	#10		1.09	0.42	0.34	0.90		
D26	200	8	#10		1.13	0.48	0.36	0.90		
D8-14-SK	25	8	1/4		1.13	0.48	0.36	0.90		
D71	200	8	1/4		1.13	0.48	0.36	0.90		
D8-516	25	8	5/16		1.32	0.59	0.49	1.03		
D72	200	8	5/16		1.32	0.59	0.49	1.03		
D8-38	25	8	3/8		1.32	0.59	0.49	1.03		
D73	200	8	3/8		1.32	0.59	0.49	1.03		
D8-12	25	8	1/2		1.49	0.82	0.55	1.09		
D75	200	8	1/2		1.49	0.82	0.55	1.09		
E6-10	20	6	#10		1.13	0.48	0.36	0.90		0.06
E26	200	6	#10		1.13	0.48	0.36	0.90		
E6-14	20	6	1/4		1.13	0.48	0.36	0.90		
E71	200	6	1/4		1.13	0.48	0.36	0.90		
E6-516	20	6	5/16		1.32	0.60	0.49	1.03		

Cat. no.	Pkg. qty.	Wire range (AWG)	Bolt hole (in.)	Rec. tool	Dimensions (in.)				Stock thick. (in.)
					A	B	C	M	
E72	200	6	5/16	TBM6S	1.32	0.60	0.49	1.03	0.06
E6-38	20	6	3/8		1.32	0.60	0.49	1.03	
E73	200	6	3/8		1.32	0.60	0.49	1.03	
E6-12	20	6	1/2		1.49	0.82	0.55	1.08	
E75	200	6	1/2		1.49	0.82	0.55	1.08	
F4-10	20	4	#10		1.16	0.48	0.36	0.93	0.07
F26	200	4	#10		1.16	0.48	0.36	0.93	
F4-14	20	4	1/4		1.16	0.48	0.36	0.93	
F71-TB	200	4	1/4		1.16	0.48	0.36	0.93	
F4-516	20	4	5/16		1.35	0.60	0.49	1.06	
F72	200	4	5/16		1.35	0.60	0.49	1.06	
F4-38	20	4	3/8		1.35	0.60	0.49	1.06	
F73	200	4	3/8		1.35	0.60	0.49	1.06	
F4-12	20	4	1/2		1.52	0.82	0.55	1.11	
F75	200	4	1/2		1.52	0.82	0.55	1.11	

Diagram

