

Ring Terminals

Non-insulated large ring terminals – Tubular



Select the configuration you need!

Non-insulated large ring terminals – Tubular



Cat. no.	Pkg. qty.	Wire range (AWG)	Bolt hole (in.)	Rec. tool	Dimensions (in.)				Stock thick. (in.)
					A	B	C	M	
D10161	200	8/8AN	#8	ERG 4005 ERG 4008	1.15	0.41	0.28	0.95	0.04
D10361	200	8/8AN	#10		1.15	0.41	0.28	0.95	
D10711	200	8/8AN	1/4		1.20	0.45	0.36	0.97	
D10721	200	8/8AN	5/16		1.28	0.56	0.36	1.00	
D10731	200	8/8AN	3/8		1.28	0.56	0.36	1.00	
D975*	200	8/8AN	1/2	TBM6S	1.46	0.83	0.49	1.06	
E10261	200	6/6AN	#10	ERG 4005 ERG 4008	1.26	0.49	0.24	1.02	0.04
E10711	200	6/6AN	1/4		1.26	0.49	0.27	0.99	
E10721	200	6/6AN	5/16		1.38	0.60	0.34	1.04	
E10731	200	6/6AN	3/8		1.38	0.60	0.34	1.04	
F10261	100	4/4AN	#10	ERG 4008	1.37	0.55	0.30	1.07	0.04
F10711	100	4/4AN	1/4		1.37	0.55	0.30	1.07	
F10721	100	4/4AN	5/16		1.42	0.62	0.34	1.08	
F10731	100	4/4AN	3/8		1.42	0.62	0.34	1.08	
F975*	200	4/4AN	1/2	TBM6S	1.49	0.83	0.45	1.10	
G926	100	2/2AN	#10	ERG 4008 TBM6S	1.59	0.69	0.40	1.26	0.04
G2-14	10	2/2AN	1/4		1.59	0.69	0.40	1.26	
G971	100	2/2AN	5/16		1.59	0.69	0.40	1.26	
G2-516	10	2/2AN	5/16		1.59	0.69	0.40	1.26	
G972	100	2/2AN	5/16		1.59	0.69	0.40	1.26	
G2-38	10	2/2AN	3/8		1.59	0.69	0.40	1.26	
G973	100	2/2AN	3/8		1.59	0.69	0.40	1.26	
G2-12	10	2/2AN	1/2		1.79	0.80	0.49	1.36	
G975	100	2/2AN	1/2		1.79	0.80	0.49	1.36	

*Braze seam.
AN – Aircraft wire

Cat. no.	Pkg. qty.	Wire range (AWG)	Bolt hole (in.)	Rec. tool	Dimensions (in.)				Stock thick. (in.)
					A	B	C	M	
H10-14	10	1AN-1/0	1/4	ERG 4008 TBM6S	1.65	0.77	0.43	1.32	0.05
H971	100	1AN-1/0	1/4		1.65	0.77	0.43	1.32	
H972	100	1AN-1/0	5/16		1.65	0.77	0.43	1.32	
H973	100	1AN-1/0	3/8		1.65	0.77	0.43	1.32	
H975	100	1AN-1/0	1/2		1.85	0.77	0.54	1.41	
J971	50	1/0AN-2/0	1/4	TBM6S	1.94	0.84	0.48	1.53	0.06
J972	50	1/0AN-2/0	5/16		1.94	0.84	0.48	1.53	
J20-38	10	1/0AN-2/0	3/8		1.84	0.83	0.46	1.46	
J973	50	1/0AN-2/0	3/8		1.99	0.84	0.53	1.58	
J974	50	1/0AN-2/0	7/16		1.99	0.89	0.51	1.56	
J975	50	1/0AN-2/0	1/2		1.99	0.89	0.51	1.56	
J976	50	1/0AN-2/0	5/8		1.99	0.89	0.51	1.56	
K971	50	2/0AN-3/0	1/4		2.08	0.93	0.54	1.69	0.06
K972	50	2/0AN-3/0	5/16		2.08	0.93	0.54	1.69	
K30-38	5	2/0AN-3/0	3/8		2.08	0.93	0.54	1.69	
K973	50	2/0AN-3/0	3/8		2.08	0.93	0.54	1.69	
K974	50	2/0AN-3/0	7/16		2.08	0.93	0.54	1.70	
K975	50	2/0AN-3/0	1/2		2.08	0.93	0.54	1.70	
L971	50	3/0AN-4/0	1/4		2.25	1.04	0.57	1.77	0.07
L972	50	3/0AN-4/0	5/16		2.25	1.04	0.57	1.77	
L40-38	5	3/0AN-4/0	3/8		2.25	1.04	0.57	1.77	
L973	50	3/0AN-4/0	3/8		2.25	1.04	0.57	1.77	
L974	50	3/0AN-4/0	7/16		2.25	1.04	0.57	1.77	
L975	50	3/0AN-4/0	1/2		2.25	1.04	0.57	1.77	
M972	50	4/0AN-250 kcmil	5/16		2.28	1.12	0.62	1.90	0.07
M250-38	5	4/0AN-250 kcmil	3/8		2.40	1.12	0.65	1.91	
M973	50	4/0AN-250 kcmil	3/8		2.40	1.12	0.65	1.91	
M974	50	4/0AN-250 kcmil	7/16		2.40	1.12	0.65	1.91	
M975	50	4/0AN-250 kcmil	1/2		2.40	1.12	0.65	1.91	

Diagram

