



### Specifications:

Material: Polyester, UL 94V-2  
 Voltage Rating: 250V  
 Current Rating: 6A  
 Withstand Voltage: 1500V AC/Minute  
 Insulation Resistance: 1000MΩ min.  
 Temperature Range: -25°C~+85°C  
 Contact Resistance: Initial value/10m max.  
 After environmental testing/20mΩ max.  
 Applicable Wire:AWG#18 TO #24

**H** **1058** — **05** **P** **S** **N** **W** **0** **0** **R**

1. PRODUCTS: H:Housing	4. CONTACT TYPE: P:Non Distribution	7. INSULATOR COLOR: W:White
2. SERIES NO.: 1058(Female Housing)	5. ROW TYPE: S:Single Row	8. FILL IT WITH "0"
3. CONTACT NO.: 01-05	6. BODY OPTION: N:W/O Ear	9. FILL IT WITH "0"
		10. R:ROHS

RoHS Compliant		LVE LAKE-VIEW ELECTRONICS	
APPD. 核准 lvy	SCALE 比例 参考	TOLERANCE 容許公差 .0 ± .00 ± ANG. ±	PART NAME 品名 1.58mm FEMALE HOUSING 1X5P WITHOUT EAR WHITE COLOR ROHS LOW-LEAD
DATE 制表日 2009/06/17	UNIT 單位 MM	SIZE 紙張尺寸 A4	PART NO. 料號 H1058-05PSNW00R
	PAGE 張數 1 OF 1	REV. 版次 A	