
THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.



NOTES:

- 1. MATERIAL:
 - BODY ALUMINUM, TIN PLATED SCREW - ALUMINUM, TIN PLATED (NOTE: LAMA6-14-QY & LAMA2-14-QY HAVE ZINC PLATED STEEL SCREWS)
- 2. cULus LISTEDFOR USE UP TO 600V & TEMPERATURE RATED 90°C (AL9CU)
- 3. DUAL RATED FOR USE WITH COPPER OR ALUMINUM STRANDED CODE CONDUCTOR
- 4. THESE PARTS ARE ROHS COMPLIANT
- 5. USE OF OXIDE INHIBITING JOINT COMPOUND LIKE PANDUIT CMP-100 RECOMMENDED FOR PAD TO PAD AND CONDUCTOR SURFACES
- 6. SEE PACKAGING LABEL FOR TIGHTENING TORQUE INFORMATION
- 7. PKG QTY: Q = 25



PART NUMBER	WIRE RANGE COPPER/ALUMINUM	WIRE STRIP LENGTH IN [mm]	STUD SIZE IN	DIMENSIONS - IN [mm]						HEX KEY*	
				A ± .03 [.8]	B ± .06 [1.5]	C ± .04 [1]	D ± .02 [.5]	E ± .04 [1]	F ± .04 [1]	G ± .02 [.5]	- NET
LAMA6-14-QY	14 AWG - 6 AWG	.38 [9.7]	1/4	.25 [6.4]	1.06 [27.0]	.37 [9.5]	.09 [2.3]	.50 [12.7]	.50 [12.7]	.43 [10.9]	SLOTTED
*LAMA6N-14-QY	14 AWG - 6 AWG	.38 [9.7]	1/4	.25 [6.4]	1.06 [27.0]	.38 [9.7]	.09 [2.4]	.38 [9.7]	.50 [12.7]	.43 [10.9]	SLOTTED
LAMA2-14-QY	14 AWG - 2 AWG	.47 [11.9]	1/4	.31 [7.9]	1.17 [29.8]	.47 [12]	.11 [2.7]	.50 [12.7]	.55 [13.9]	.38 [9.7]	SLOTTED
LAMA1/0-14-QY	14 AWG - 1/0 AWG	.63 [15.9]	1/4	.42 [10.7]	1.47 [37.3]	.63 [15.9]	.19 [4.8]	.62 [15.7]	.77 [19.5]	.43 [10.9]	SLOTTED
LAMA1/0-56-Q	14 AWG - 1/0 AWG	.62 [15.7]	5/16	.25 [6.4]	1.47 [37.3]	.62 [15.7]	.19 [4.8]	.62 [15.7]	.79 [20.0]	.60 [15.2]	SLOTTED
LAMA2/0-14-QY	14 AWG - 2/0 AWG	.62 [5.7]	1/4	.44 [11.2]	1.46 [37.1]	.63 [15.9]	.19 [4.8]	.63 [15.9]	.77 [19.5]	.41 [10.4]	3/16
LAMA250-56-QY	6 AWG - 250 kcmil	1.00 [25.4]	5/16	.45 [11.5]	1.99 [50.5]	1.00 [25.3]	.25 [6.4]	.99 [25.2]	1.12 [28.4]	.56 [14.2]	5/16

^{*}LAMA6N-14-QY ONLY AVAILABLE IN ASIA-PACIFIC REGION

							LAMA SERIES 6AWG THRU 250kcmil ALUMINUM MECHANICAL LUGS CUSTOMER DRAWING
							DATASET FILE NAME 10N006 A.R. N.C. (18. S.L. D.D.D.W.)
17	1/2020	JHNU	RGB	RGB	REVISED B DIM FOR LAMA2/0-14-QY: 1.46 [37.1] WAS 1.47 [37.3] REVISED C DIM FOR LAMA2/0-14-QY: .63 [15.9] WAS .62 [15.7] REVISED D DIM FOR LAMA2/0-14-QY: .19 [4.9] WAS .19 [4.8] REVISED E DIM FOR LAMA2/0-14-QY: .63 [15.9] WAS .62 [15.8] REVISED F DIM FOR LAMA2/0-14-QY: .77 [19.5] WAS .79 [20.0] REVISED B DIM FOR LAMA250-56-QY: 1.99 [50.5] WAS 2.01 [51.0] REVISED C DIM FOR LAMA250-56-QY: 1.00 [25.3] WAS 1.00 [25.4] REVISED F DIM FOR LAMA250-56-QY: 1.12 [28.4] WAS 1.13 [28.6]	057109	10N006AR-NC/18.SLDDRW UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: IN [mm] .X ± .XXX ± .XX ± ANGLES ± THIRD ANGLE PROJECTION TON006AR-NC
REV	DATE	BY	CHK	APR	DESCRIPTION	ECN	DRAWN BY DATE CHK SCALE NONE SHEET 1 OF 1 B