Incandescent Pilot Lights





PL-116 Series • 12V Single Contact, Insulated Pilot Light

- #1893 bulb supplied, Aluminum bezel
- Plastic socket

PART NUMBERS			RATING	LENS COLOR	TERMINALS	BEZEL SIZE	LENS SIZE
BULK	BOXED	RETAIL	IIAIIIVO	LLIVO GOLOII	TEHWHINALO	DLZLE OIZE	LLIVO OIZL
-	PL-116-RC000-BX	-	12V DC	Red	None	15/16" (23.8mm) Ø	5/8" (15.9mm) Ø

PL-118 Series • 12V Single Contact, Insulated Pilot Lights

- Mounts through rear of the panel. #1893 bulb supplied. Satin finish or black aluminum bezel.
- 11/16" (7.5mm) diameter mounting stem, 1/4" (6.4mm) long.



PA	RATING	LENS	BEZEL	TERMINALS	BEZEL SIZE	LENS SIZE		
BULK	BOXED	RETAIL	TIATING	COLOR	COLOR	TEHWHYALO	DLZLL OIZL	LLIVO OIZL
PL-118-RC000	PL-118-RC000-BX	_	12V DC	Red	Satin Silver	2x 8" wire leads	15/16" (23.8mm) Ø	5/8" (15.9mm) Ø
PL-118-RC001	PL-118-RC001-BX	-	12V DC	Red	Black	2x 8" wire leads	15/16" (23.8mm) Ø	5/8" (15.9mm) Ø
PL-118-GC001	PL-118-GC001-BX	_	12V DC	Green	Black	2x 8" wire leads	15/16" (23.8mm) Ø	5/8" (15.9mm) Ø
PL-118-AC001	-	-	12V DC	Amber	Black	2x 8" wire leads	15/16" (23.8mm) Ø	5/8" (15.9mm) Ø

M-320 Series • 12V Single Contact, Insulated with Smooth Lens

- #53 bulb supplied, Chrome-plated brass bezel
- · Plastic socket
- 3/4" (19.1mm) diameter mounting stem, 1 1/16" (27.0mm) long.





Panel Lamps and Base Sockets

12V Bayonet Base Sockets

- Accept incandescent or LED bulbs with corresponding bases.
- Suggested lamp numbers for BA15s sockets: 63, 67, 81, 87, 93, 97,103, 209,1073, 1129, 1133, 1141, 1156.
- 16AWG insulated stranded copper leads 8" (203mm) long









3575



2611

PART NUMBERS		RATING	LAMPS	MOUNTING	TERMINALS	CONTACT	NOTES		
BULK	BOXED	RETAIL	HAIINU	ACCEPTED	MOONTING	TEHIVIIIVALO	TYPE	NOTES	
-	_	26100-BP			Without Flange	2x Wire	Double	11/16" outside diameter Molded plastic insulator	
2609	2609-BX	-	12V DC	BA15d	Side bracket with 3/16" (4.8mm) Ø hole	1x Wire	Single	-	
M-432	M-432-BX	M-432-BP	IZV DC	DAISU	Standard Base	2 Screw	Double	Marine Socket	
M-458	M-458-BX	-			Standard Base	2 Wire	Double	Marine Dash Assembly	





DL Series • 12V Single Contact, Grounding Panel Lamps

- Self-grounding to metal panels
- For illumination of maps or other items, with minimal interference of driving visibility
- Hood can be rotated to direct the light beam
- 11/16" (17.5mm) diameter mounting stem, 3/8" (9.5mm) long; mount through the panel.
- 16AWG insulated stranded copper leads

PART NUMBERS			S	RATING	COLOR	MATERIAL	TERMINALS	
BUI	_K	BOXED	RETAIL	HAIING	COLOII	IVIALLITIAL	TEHIVIIIVALO	
DL-	13	DL-13-BX	_	12V DC	Chrome-plated	Brass	1x 8" wire leads	
DL-2	21	DL-21-BX	-	12V DC	Black	Steel	1x 8" wire leads	