

Fork terminals

Vinyl-insulation forks & vinyl-insulated locking forks




Vinyl-insulation forks – Expanded insulation



Cat. no.	Pkg. qty.	Wire range (AWG)	Max. ins. (in.)	Bolt hole (in.)	Rec. tool	Dimensions (in.)				Stock thick. (in.)
						A	B	C	M	
18RA-6FX	100	22-16	0.170	#6	ERG4001	0.94	0.25	0.27	0.81	0.02
RA1167-170	1,000	22-16	0.170	#6		0.94	0.25	0.27	0.81	0.02
18RA-8FX	100	22-16	0.170	#8		0.97	0.31	0.27	0.81	0.02
RA1147-170	1,000	22-16	0.170	#8		0.97	0.31	0.27	0.81	0.02
18RA-10FX	100	22-16	0.170	#10		0.97	0.31	0.27	0.81	0.02
RA1157-170	1,000	22-16	0.170	#10		0.97	0.31	0.27	0.81	0.02
14RB-6FX	100	18-14	0.200	#6		0.97	0.31	0.27	0.81	0.03
RB647-200	1,000	18-14	0.200	#6		0.97	0.31	0.27	0.81	0.03
14RB-8FX	100	18-14	0.200	#8		0.97	0.31	0.27	0.81	0.03
RB657-200	1,000	18-14	0.200	#8		0.97	0.31	0.27	0.81	0.03
14RB-10FX	100	18-14	0.200	#10		0.97	0.31	0.27	0.81	0.03
RB1157-200	1,000	18-14	0.200	#10		0.97	0.31	0.27	0.81	0.03
10RC-8FX	50	12-10	0.250	#8		1.11	0.38	0.27	0.90	0.04
RC1147-250	500	12-10	0.250	#8		1.11	0.38	0.27	0.90	0.04
10RC-10FX	50	12-10	0.250	#10		1.11	0.38	0.27	0.90	0.04
RC1157-250	500	12-10	0.250	#10		1.11	0.38	0.27	0.90	0.04
10RC-14FX	50	12-10	0.250	¼		1.17	0.50	0.37	0.90	0.04

Diagram




Vinyl-insulated locking forks



Cat. no.	Pkg. qty.	Wire range (AWG)	Max. ins. (in.)	Bolt hole (in.)	Rec. tool	Dimensions (in.)				Stock thick. (in.)
						A	B	C	M	
18RA-6FL	100	22-16	0.150	#6	ERG4001	0.97	0.25	0.25	0.81	0.02
RA2217	1,000	22-16	0.150	#6		0.97	0.25	0.25	0.81	0.02
RA2227	1,000	22-16	0.155	#6		0.97	0.29	0.25	0.81	0.02
18RA-8FL	100	22-16	0.150	#8		0.97	0.29	0.25	0.81	0.02
RA2247	1,000	22-16	0.150	#8		0.97	0.29	0.25	0.81	0.02
18RA-10FL	100	22-16	0.150	#10		0.97	0.29	0.25	0.81	0.02
RA2257	1,000	22-16	0.150	#10		0.97	0.29	0.25	0.81	0.02
14RB-6FL	100	18-14	0.170	#6		0.97	0.25	0.27	0.81	0.03
RB2207	1,000	18-14	0.170	#6		0.97	0.25	0.27	0.81	0.03
RB2217	1,000	18-14	0.170	#6		0.97	0.29	0.27	0.81	0.03
14RB-8FL	100	18-14	0.170	#8		0.97	0.29	0.27	0.81	0.03
RB2237	1,000	18-14	0.170	#8		0.97	0.29	0.27	0.81	0.03
14RB-10FL	100	18-14	0.170	#10		0.97	0.29	0.27	0.81	0.03
RB2257	1,000	18-14	0.170	#10		0.97	0.29	0.27	0.81	0.03
10RC-6FL	50	12-10	0.220	#6		1.09	0.31	0.27	0.90	0.04
RC2207	500	12-10	0.220	#6		1.09	0.31	0.27	0.90	0.04
10RC-8FL	50	12-10	0.220	#8		1.09	0.37	0.27	0.90	0.04
RC2217	500	12-10	0.220	#8		1.09	0.37	0.27	0.90	0.04
10RC-10FL	50	12-10	0.220	#10		1.09	0.37	0.27	0.90	0.04
RC2227	500	12-10	0.220	#10		1.09	0.37	0.27	0.90	0.04
10RC-14FL	50	12-10	0.220	¼		1.09	0.49	0.27	0.90	0.04
RC2237	500	12-10	0.220	¼		1.09	0.49	0.27	0.90	0.04

Diagram



For multiple wire combinations per UL® file E9609, see page 14.

For multiple wire combinations per UL file E9609, see page 14.