

## Ring terminals

Nylon-insulated ring terminals



Nylon-insulated ring terminals (continued)



Cat. no.	Wire Pkg. qty.	Max. range (AWG)	Bolt ins. hole (in.)	Rec. tool	Dimensions (in.)				Stock thick. (in.)	
					A	B	C	M		
RB14-4	100	18-14	0.162	#4	ERG4001	0.72	0.26	0.14	0.59	0.03
RB1323	1,000	18-14	0.162	#4		0.72	0.26	0.14	0.59	
RB14-6	100	18-14	0.162	#6		0.89	0.31	0.25	0.71	
RB853	1,000	18-14	0.162	#6		0.89	0.31	0.25	0.71	
RB1333	1,000	18-14	0.162	#6		0.74	0.26	0.14	0.59	
RB14-8	100	18-14	0.162	#8		0.89	0.31	0.25	0.71	
RB863	1,000	18-14	0.162	#8		0.89	0.31	0.25	0.71	
RB14-10	100	18-14	0.162	#10		0.89	0.31	0.25	0.71	
RB873	1,000	18-14	0.162	#10		0.89	0.31	0.25	0.71	
RB14-14	100	18-14	0.162	1/4		1.08	0.47	0.31	0.81	
RB713	1,000	18-14	0.162	1/4		1.08	0.47	0.31	0.81	
RB14-516	100	18-14	0.162	5/16		1.08	0.47	0.31	0.84	
RB723	1,000	18-14	0.162	5/16		1.08	0.47	0.31	0.84	
RB14-38	100	18-14	0.162	3/8		1.17	0.53	0.35	0.87	
RB733	1,000	18-14	0.162	3/8		1.17	0.53	0.35	0.87	
RB14-12	100	18-14	0.162	1/2		1.25	0.72	0.50	0.90	
RB753	1,000	18-14	0.162	1/2		1.25	0.72	0.50	0.90	
RC10-6	50	12-10	0.210	#6	ERG4001	1.00	0.37	0.27	0.81	0.04
RC333	500	12-10	0.210	#6		1.00	0.37	0.27	0.81	
RC10-8	50	12-10	0.210	#8		1.00	0.37	0.27	0.81	
RC863	500	12-10	0.210	#8		1.00	0.37	0.27	0.81	
RC10-10	50	12-10	0.210	#10		1.00	0.37	0.27	0.81	
RC363	500	12-10	0.210	#10		1.00	0.37	0.27	0.81	
RC10-14	50	12-10	0.210	1/4		1.12	0.53	0.32	0.86	
RC713	500	12-10	0.210	1/4		1.12	0.53	0.32	0.86	
RC10-516	50	12-10	0.210	5/16		1.21	0.53	0.31	0.94	
RC703	500	12-10	0.210	5/16		1.21	0.53	0.31	0.94	
RC10-38	50	12-10	0.210	3/8		1.27	0.59	0.35	0.98	
RC733	500	12-10	0.210	3/8		1.27	0.59	0.35	0.98	
RC10-12	50	12-10	0.210	1/2		1.37	0.72	0.52	1.02	
RC753	500	12-10	0.210	1/2		1.37	0.72	0.52	1.02	




Nylon-insulated ring terminals – Expanded entry



Cat. no.	Wire Pkg. qty.	Max. range (AWG)	Bolt ins. hole (in.)	Rec. tool	Dimensions (in.)				Stock thick. (in.)	
					A	B	C	M		
RB14-4X	100	18-14	0.190	#4	ER4001	0.80	0.26	0.14	0.67	0.03
RB14-6X	100	18-14	0.190	#6		0.95	0.31	0.25	0.79	
RB854	1,000	18-14	0.190	#6		0.95	0.31	0.25	0.79	
RB14-8X	100	18-14	0.190	#8		0.95	0.31	0.25	0.79	
RB864	1,000	18-14	0.190	#8		0.95	0.31	0.25	0.79	
RB14-10X	100	18-14	0.190	#10		0.95	0.31	0.25	0.79	
RB874	1,000	18-14	0.190	#10		0.95	0.31	0.25	0.79	
RB14-14X	100	18-14	0.190	1/4		1.16	0.47	0.31	0.92	
RB714	1,000	18-14	0.190	1/4		1.16	0.47	0.31	0.92	
RB14-516X	100	18-14	0.190	5/16		1.16	0.47	0.31	0.92	
RB724	1,000	18-14	0.190	5/16		1.16	0.47	0.31	0.92	
RB14-38X	100	18-14	0.190	3/8		1.25	0.53	0.42	0.95	
RB734	1,000	18-14	0.190	3/8		1.25	0.53	0.42	0.95	
RC10-6X	50	12-10	0.250	#6	ERG4001	1.10	0.37	0.27	0.91	0.04
RC334	500	12-10	0.250	#6		1.10	0.37	0.27	0.91	
RC10-8X	50	12-10	0.250	#8		1.10	0.37	0.27	0.91	
RC864	500	12-10	0.250	#8		1.10	0.37	0.27	0.91	
RC10-10X	50	12-10	0.250	#10		1.10	0.37	0.27	0.91	
RC364	500	12-10	0.250	#10		1.10	0.37	0.27	0.91	
RC10-14X	50	12-10	0.250	1/4		1.22	0.53	0.32	0.96	
RC714	500	12-10	0.250	1/4		1.22	0.53	0.32	0.96	
RC10-516X	50	12-10	0.250	5/16		1.32	0.53	0.31	1.05	
RC704	500	12-10	0.250	5/16		1.32	0.53	0.31	1.05	
RC10-38X	50	12-10	0.250	3/8		1.38	0.59	0.48	1.09	
RC734	500	12-10	0.250	3/8		1.38	0.59	0.48	1.09	
RC10-12X	50	12-10	0.250	1/2		1.48	0.72	0.52	1.13	

Diagram



Diagram

