

Ring terminals

Nylon-insulated large ring terminals




Nylon-insulated large ring terminals (continued)



Cat. no.	Pkg. qty.	Wire range (AWG)	Max. ins. (in.)	Bolt hole (in.)	Rec. tool	Dimensions (in.)				Stock thick. (in.)
						A	B	C	M	
Flex class 105/24										
RG2-10	10	2	0.588	#10	TBM6S	2.15	0.69	0.40	1.83	0.05
RG267	50	2	0.588	#10		2.15	0.69	0.40	1.83	
RG2-14	10	2	0.588	¼		2.15	0.69	0.40	1.83	
RG717	50	2	0.588	¼		2.15	0.69	0.40	1.83	
RG2-516	10	2	0.588	5/16		2.15	0.69	0.40	1.83	
RG727	50	2	0.588	5/16		2.15	0.69	0.40	1.83	
RG2-38	10	2	0.588	3/8		2.15	0.69	0.40	1.83	
RG737	50	2	0.588	3/8		2.15	0.69	0.40	1.83	
RG2-12	10	2	0.588	½		2.35	0.80	0.49	1.93	
RG757	50	2	0.588	½		2.35	0.80	0.49	1.93	
RG9711	50	2AN	0.453	¼		2.07	0.69	0.40	1.74	
RG9731	50	2AN	0.453	3/8		2.07	0.69	0.40	1.74	
RG9751	50	2AN	0.453	½		2.26	0.80	0.49	1.84	
RH717	50	1/0	0.629	¼		2.14	0.77	0.43	1.81	0.05
RH727	50	1/0	0.629	5/16		2.14	0.77	0.43	1.81	
RH737	50	1/0	0.629	3/8		2.14	0.77	0.43	1.81	
RH757	50	1/0	0.629	½		2.34	0.77	0.54	1.90	
RH9711	50	1AN	0.500	¼		2.14	0.77	0.44	1.81	
RH9731	50	1AN	0.500	3/8		2.14	0.77	0.44	1.81	
RH9751	50	1AN	0.500	½		2.34	0.77	0.54	1.90	
RJ717	100	2/0	0.675	¼		2.34	0.83	0.46	1.96	0.06
RJ727	100	2/0	0.675	5/16		2.34	0.83	0.46	1.96	
RJ737	100	2/0	0.675	3/8		2.34	0.83	0.46	1.96	
RJ757	100	2/0	0.675	½		2.48	0.89	0.54	2.03	
RJ9711	50	1/0AN	0.550	¼		2.35	0.83	0.46	1.97	
RJ9731	50	1/0AN	0.550	3/8		2.35	0.83	0.46	1.97	
RJ9751	50	1/0AN	0.550	½		2.49	0.89	0.55	2.04	

Cat. no.	Pkg. qty.	Wire range (AWG)	Max. ins. (in.)	Bolt hole (in.)	Rec. tool	Dimensions (in.)				Stock thick. (in.)
						A	B	C	M	
Flex class 105/24										
RK717	25	3/0	0.765	¼	TBM6S	2.60	0.93	0.54	2.21	0.06
RK727	25	3/0	0.765	5/16		2.60	0.93	0.54	2.21	
RK737	25	3/0	0.765	3/8		2.60	0.93	0.54	2.21	
RK9731	100	2/0AN	0.610	3/8		2.52	0.93	0.55	2.14	
RK9751	100	2/0AN	0.610	½		2.60	0.93	0.55	2.15	
RL737	25	4/0	0.785	3/8		2.83	1.04	0.57	2.35	0.07
RL757	25	4/0	0.785	½		2.83	1.04	0.57	2.35	
RL9731	25	3/0AN	0.680	3/8		2.83	1.04	0.57	2.36	
RL9751	25	3/0AN	0.680	½		2.83	1.04	0.57	2.36	
RM737	20	250 kcmil	0.868	3/8		3.00	1.13	0.65	2.51	0.07
RM747	20	250 kcmil	0.868	7/16		3.00	1.13	0.65	2.51	
RM757	20	250 kcmil	0.868	½		3.00	1.13	0.65	2.51	
RM9731	20	4/0AN	0.750	3/8		3.00	1.13	0.66	2.51	
RM9751	20	4/0AN	0.750	½		3.00	1.13	0.66	2.51	

Diagram



*Braided seam
AN = Aircraft wire