

Catamount® Terminals



Vinyl Insulated Female Disconnects — 250 Series 

| CAT. NO. | WIRE RANGE | PKG. QTY. |
|------------|------------|-----------|
| TV18-250FD | 22-16 | 50 |
| TV14-250FD | 16-14 | 50 |
| TV10-250FD | 12-10 | 25 |



Nylon Fully Insulated Female Disconnects — 250 Series 

| CAT. NO. | WIRE RANGE | PKG. QTY. |
|-------------|------------|-----------|
| TNF18-250FD | 22-16 | 50 |
| TNF14-250FD | 16-14 | 50 |
| TNF10-250FD | 12-10 | 25 |



Vinyl Fully Insulated Female Disconnects — 250 Series 

| CAT. NO. | WIRE RANGE | PKG. QTY. |
|-------------|------------|-----------|
| TVF18-250FD | 22-16 | 50 |
| TVF14-250FD | 16-14 | 50 |
| TVF10-250FD | 12-10 | 25 |



Vinyl Insulated Male Disconnects — 250 Series 

| CAT. NO. | WIRE RANGE | PKG. QTY. |
|------------|------------|-----------|
| TV18-250MD | 22-16 | 50 |
| TV14-250MD | 16-14 | 50 |
| TV10-250MD | 12-10 | 25 |



Nylon Fully Insulated Male Disconnects — 250 Series 


| CAT. NO. | WIRE RANGE | PKG. QTY. |
|-------------|------------|-----------|
| TNF18-250MD | 22-16 | 50 |
| TNF14-250MD | 16-14 | 50 |
| TNF10-250MD | 12-10 | 25 |



Vinyl Insulated Piggyback Disconnects — 250 Series 

| CAT. NO. | WIRE RANGE | PKG. QTY. |
|------------|------------|-----------|
| TV18-250PD | 22-16 | 50 |
| TV14-250PD | 16-14 | 50 |
| TV10-250PD | 12-10 | 25 |



Vinyl Fully Insulated Female Bullet Connectors — 4mm (.156") 

| CAT. NO. | WIRE RANGE | PKG. QTY. |
|-----------|------------|-----------|
| TVF18-4FB | 22-16 | 50 |



Nylon Fully Insulated Female Bullet Connectors 

| CAT. NO. | WIRE RANGE | PKG. QTY. |
|-----------|------------|-----------|
| TNF18-4FB | 22-16 | 50 |
| TNF14-4FB | 16-14 | 50 |



Vinyl Insulated Straight Blade Terminals 

| CAT. NO. | WIRE RANGE | PKG. QTY. |
|-----------|------------|-----------|
| TV18-10BL | 22-16 | 50 |
| TV18-18BL | | 50 |
| TV14-10BL | 16-14 | 50 |
| TV14-18BL | | 50 |
| TV10-10BL | 12-10 | 25 |



Vinyl Insulated Male Bullet Connectors — 4mm (.156") 

| CAT. NO. | WIRE RANGE | PKG. QTY. |
|----------|------------|-----------|
| TV18-4MB | 22-16 | 50 |
| TV14-4MB | 16-14 | 50 |



Fully Insulated Nylon Male Bullet Connectors 

| CAT. NO. | WIRE RANGE | PKG. QTY. |
|-----------|------------|-----------|
| TNF18-4MB | 22-16 | 50 |
| TNF14-4MB | 16-14 | 50 |



Vinyl Insulated Straight Pin Terminals 

| CAT. NO. | WIRE RANGE | PKG. QTY. |
|-----------|------------|-----------|
| TV18-12PT | 22-16 | 50 |
| TV14-12PT | 16-14 | 50 |
| TV10-14PT | 12-10 | 25 |