



16/14 Male Slip-Ons

650°F

CMA Range 2050-5180

Barrel Inside Diameter .085/ 2.16 mm



Material: NICKEL PLATED BRASS
Thickness: .032" / .813 mm

Basic Dimensions				Non-Insulated			
NEMA TAB	C In.	C mm	NIT Brazed	E In.	E mm	L In.	L mm
.032 x .187	.125	7.11	SO9017S	.250	6.35	0.62	15.75
.032 x .205	.125	7.11	SO9018S	.250	6.35	0.62	15.75
.032 x .250	.150	7.11	SO9019S	.312	7.92	0.67	17.02
Hand Tool	H4A						





18/14 Male Slip-Ons

900°F

Also available in 1200°F Nickel

CMA Range 1600-5180

Barrel Inside Diameter .085/ 2.16 mm




Material: NICKEL PLATED STEEL ALLOY
Thickness: .032" / .813 mm

Basic Dimensions				Non-Insulated			
NEMA TAB	C In.	C mm	NIT	E In.	E mm	L In.	L mm
.032x.187	.125	3.18	SO9012S	.250	6.35	.62	15.75
.020x.205	.134	3.18	SO9015S	.250	6.35	.62	15.75
.032x.250	.134	3.40	SO9016S †	.312	7.92	.67	17.02
Hand Tool	H16HT						



22/10 Butt connectors 650°F - 900°F



Material: NICKEL PLATED COPPER **Material: NICKEL PLATED STEEL ALLOY**

Basic Dimensions		Non-Insulated							
		650°F				900°F			
Wire Size	CMA Range	NIT Brazed	I.D. In.	I.D. mm	O.D. In.	O.D. mm	L In.	L mm	
22-16	509-3260	B1843B	.061	1.55	.136	3.45	.58	14.73	
16-14	2050-5180	B1846B	.065	2.16	.159	4.04	.58	14.73	
12-10	5180-13,100	B1853B	.131	3.33	.221	5.61	.74	18.80	
Hand Tool	H4A		H16HT						



Female Slip-Ons



900°F

18/14 CMA Range 1600-5180

Barrel Inside Diameter .081/ 2.06 mm

12/10 CMA Range 5100-13,100

Barrel Inside Diameter .130/ 3.30 mm



Material: NICKEL PLATED STEEL ALLOY
Thickness: .018" / .457 mm

Basic Dimensions					Non-Insulated					
NEMA TAB	W In.	W mm	T In.	T mm	NIT	E In.	E mm	L In.	L mm	HAND TOOL
.020x.187	.233	5.92	.026	.660	SO9750S	.250	6.35	.59	14.99	H12
.032x.187	.233	5.92	.026	.660	SO9751S	.250	6.35	.59	14.99	H12
.020x.205	.250	6.35	.026	.660	SO9752S	.250	6.35	.59	14.99	H12
.032x.205	.250	6.35	.026	.660	SO9753S	.250	6.35	.59	14.99	H12
.032x.250	.296	7.52	.065	1.65	SO9754S	.300	7.62	.64	16.26	H12
.032x.250	.300	7.62	.065	1.65	SO9214 *	.300	7.62	.72	18.29	

* 12/10 AWG



Most terminals available tape mounted.
Consult Electro-Term/Hollinsworth with your specifications.

